



IEC 61158-6-12

Edition 1.0 2007-12

INTERNATIONAL STANDARD

**Industrial communication networks – Fieldbus specifications –
Part 6-12: Application layer protocol specification – Type 12 elements**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

XF

ICS 35.100.70; 25.040.40

ISBN 2-8318-9487-5

CONTENTS

FOREWORD.....	7
INTRODUCTION.....	9
1 Scope.....	10
1.1 General.....	10
1.2 Specifications.....	11
1.3 Conformance.....	11
2 Normative references.....	11
3 Terms, definitions, symbols, abbreviations and conventions.....	12
3.1 Reference model terms and definitions.....	12
3.2 Service convention terms and definitions.....	12
3.3 Application layer definitions.....	13
3.4 Common symbols and abbreviations.....	18
3.5 Additional symbols and abbreviations.....	18
3.6 Conventions.....	19
4 Application Layer protocol specification.....	24
4.1 Operating principle.....	24
4.2 Node reference model.....	24
5 FAL syntax description.....	26
5.1 Coding principles.....	26
5.2 Data types and encoding rules.....	26
5.3 AR coding.....	29
5.4 SII coding.....	34
5.5 Isochronous PDI coding.....	39
5.6 CoE coding.....	42
5.7 EoE coding.....	79
5.8 FoE Coding.....	88
6 FAL protocol state machines.....	94
6.1 Overall structure.....	94
6.2 AP-Context state machine.....	96
6.3 FAL service protocol machine (FSPM).....	96
6.4 Application Relationship Protocol Machines (ARPMs).....	96
6.5 DLL mapping protocol machine (DMPM).....	135
Bibliography.....	136
Figure 1 – Common structure of specific fields.....	20
Figure 2 – Type description example.....	21
Figure 3 – Slave Node Reference Model.....	25
Figure 4 – Encoding of Time Of Day value.....	26
Figure 5 – Encoding of Time Difference value.....	27
Figure 6 – AL Control Request structure.....	29
Figure 7 – AL Control Response structure.....	30
Figure 8 – AL State Changed structure.....	32
Figure 9 – PDI Control type description.....	32
Figure 10 – Sync Configuration type description.....	33

Figure 11 – Distributed Clock sync and latch type description	39
Figure 12 – CoE general structure	42
Figure 13 – SDO Download Expedited Request structure	43
Figure 14 – SDO Download Expedited Response structure	44
Figure 15 – SDO Download Normal Request structure	45
Figure 17 – Download SDO Segment Request structure	47
Figure 18 – Download SDO Segment Response structure	47
Figure 19 – SDO Upload Expedited Request structure	48
Figure 20 – SDO Upload Expedited Response structure	49
Figure 22 – SDO Upload Normal Response structure	50
Figure 23 – Upload SDO Segment Request structure	51
Figure 24 – Upload SDO Segment Response structure	52
Figure 25 – Abort SDO Transfer Request structure	53
Figure 26 – SDO Information Service structure	55
Figure 27 – Get OD List Request structure	56
Figure 28 – Get OD List Response structure	57
Figure 29 – Get Object Description Request structure	58
Figure 30 – Get Object Description Response structure	59
Figure 31 – Get Entry Description Request structure	60
Figure 32 – Get Entry Description Response structure	61
Figure 33 – SDO Info Error Request structure	63
Figure 34 – EoE general structure	79
Figure 35 – EoE Timestamp structure	80
Figure 36 – EoE Fragment Request structure	81
Figure 37 – Set IP Parameter Request structure	83
Figure 38 – Set IP Parameter Response structure	85
Figure 39 – Set Address Filter Request structure	86
Figure 40 – Set Address Filter Response structure	88
Figure 41 – Read Request structure	89
Figure 42 – Write Request structure	89
Figure 43 – Data Request structure	90
Figure 44 – Ack Request structure	91
Figure 45 – Error Request structure	92
Figure 46 – Busy Request structure	94
Figure 47 – Relationship among Protocol Machines	95
Figure 48 – AR Protocol machines	96
Figure 49 – ESM Diagramm	98
Table 1 – PDU element description example	21
Table 2 – Example attribute description	22
Table 3 – State machine description elements	22
Table 4 – Description of state machine elements	23
Table 5 – Conventions used in state machines	23

Table 6 – Transfer Syntax for bit sequences	27
Table 7 – Transfer syntax for data type Unsignedn	28
Table 8 – Transfer syntax for data type Integern	29
Table 9 – AL Control Description	30
Table 10 – AL Control Response	30
Table 11 – AL Status Codes	31
Table 12 – AL State Changed	32
Table 13 – PDI Control	33
Table 14 – PDI Configuration	33
Table 15 – Sync Configuration	33
Table 16 – Slave Information Interface Area	34
Table 17 – Slave Information Interface Categories	35
Table 18 – Mailbox Protocols Supported Types	35
Table 19 – Categories Types	36
Table 20 – Structure Category String	36
Table 21 – Structure Category General	37
Table 22 – Structure Category FMMU	38
Table 23 – Structure Category SyncM for each Element	38
Table 24 – Structure Category TXPDO and RXPDO for each PDO	38
Table 25 – Structure PDO Entry	39
Table 26 – Distributed Clock sync parameter	40
Table 27 – Distributed Clock latch data	41
Table 28 – CoE elements	42
Table 29 – SDO Download Expedited Request	44
Table 30 – SDO Download Expedited Response	45
Table 31 – SDO Download Normal Request	46
Table 33 – Download SDO Segment Request	47
Table 34 – Download SDO Segment Response	48
Table 35 – SDO Upload Expedited Request	49
Table 36 – SDO Upload Expedited Response	50
Table 38 – SDO Upload Normal Response	51
Table 39 – Upload SDO Segment Request	52
Table 40 – Upload SDO Segment Response	53
Table 41 – Abort SDO Transfer Request	54
Table 42 – SDO Abort Codes	55
Table 43 – SDO Information Service	56
Table 44 – Get OD List Request	57
Table 45 – Get OD List Response	58
Table 46 – Get Object Description Request	59
Table 47 – Get Object Description Response	60
Table 48 – Get Entry Description Request	61
Table 49 – Get Entry Description Response	62
Table 50 – SDO Info Error Request	63

Table 51 – Emergency Request.....	64
Table 52 – Emergency Error Codes	65
Table 53 – Error Code	65
Table 54 – Diagnostic Data	66
Table 55 – Sync Manager Length Error.....	66
Table 56 – Sync Manager Address Error	66
Table 57 – Sync Manager Settings Error.....	66
Table 58 – RxPDO Transmission via mailbox	67
Table 59 – TxPDO Transmission via mailbox.....	67
Table 60 – RxPDO Remote Transmission Request	68
Table 61 – TxPDO Remote Transmission Request	68
Table 62 – Command object structure	69
Table 63 – Object Dictionary Structure	69
Table 64 – Object Code Definitions	69
Table 65 – Basic Data Type Area	70
Table 66 – Extended Data Type Area	71
Table 67 – Enumeration Definition.....	72
Table 67 – CoE Communication Area	72
Table 68 – Device Type.....	73
Table 70 – Error Register	74
Table 69 – Manufacturer Device Name	74
Table 70 – Manufacturer Hardware Version	75
Table 71 – Manufacturer Software Version	75
Table 72 – Identity Object.....	75
Table 73 – Receive PDO Mapping	76
Table 74 – Transmit PDO Mapping	76
Table 75 – Sync Manager Communication Type	77
Table 76 – Sync Manager Channel 0 (Mailbox Receive).....	77
Table 77 – Sync Manager Channel 1 (Mailbox Send)	77
Table 78 – Sync Manager Channel 2 (Process Data Output)	78
Table 79 – Sync Manager Channel 3 (Process Data Input).....	78
Table 80 – Sync Manager Channel 4-32	78
Table 81 – Sync Manager Synchronization	79
Table 82 – Initiate EoE Request	80
Table 83 – Initiate EoE Response.....	81
Table 84 – EoE Fragment Request.....	82
Table 85 – EoE Data	83
Table 86 – Set IP Parameter Request.....	84
Table 87 – Set IP Parameter Response	85
Table 88 – EoE Result Parameter	86
Table 89 – Set Address Filter Request	87
Table 90 – Set Address Filter Response.....	88
Table 91 – Read Request.....	89

Table 92 – Write Request.....	90
Table 93 – Data Request.....	91
Table 94 – Ack Request	92
Table 95 – Error Request	93
Table 96 – Error codes of FoE.....	93
Table 97 – Busy Request	94
Table 98 – State transitions and local management services	98
Table 99 – Primitives issued by ESM to DL.....	99
Table 100 – Primitives issued by DL to ESM.....	99
Table 101 – Primitives issued by Application to ESM	100
Table 102 – Primitives issued by ESM to Application	100
Table 103 – ESM state table	101
Table 104 – ESM Functions.....	109
Table 105 – Primitives issued by Mailbox handler to DL.....	110
Table 106 – Primitives issued by DL to Mailbox handler.....	110
Table 107 – Primitives issued by Protocol handler to Mailbox handler	110
Table 108 – Primitives issued by Mailbox handler to Protocol handler	111
Table 109 – Primitives issued by Application to CoESM	112
Table 110 – Primitives issued by CoESM to Application	113
Table 111 – CoESM state table	113
Table 112 – Primitives issued by Application to EoESM	124
Table 113 – Primitives issued by EoESM to Application	125
Table 114 – EoESM state table	126
Table 115 – Primitives issued by Application to FoESM	130
Table 116 – Primitives issued by FoESM to Application	131
Table 117 – FoESM state table.....	131

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**INDUSTRIAL COMMUNICATION NETWORKS –
FIELDBUS SPECIFICATIONS –****Part 6-12: Application layer protocol specification – Type 12 elements**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

NOTE Use of some of the associated protocol Types is restricted by their intellectual-property-right holders. In all cases, the commitment to limited release of intellectual-property-rights made by the holders of those rights permits a particular data-link layer protocol Type to be used with physical layer and application layer protocols in Type combinations as specified explicitly in the IEC 61784 series. Use of the various protocol Types in other combinations may require permission of their respective intellectual-property-right holders.

International Standard IEC 61158-6-12 has been prepared by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

This first edition and its companion parts of the IEC 61158-6 series cancel and replace IEC 61158-6:2003. This edition of this part constitutes a technical addition. This part also replaces IEC/PAS 62407, published in 2005

This edition of IEC 61158-6 includes the following significant changes from the previous edition:

- a) deletion of the former Type 6 fieldbus for lack of market relevance;

- b) addition of new types of fieldbuses;
- c) partition of part 6 of the third edition into multiple parts numbered -6-2, -6-3, ...

The text of this standard is based on the following documents:

FDIS	Report on voting
65C/476/FDIS	65C/487/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under <http://webstore.iec.ch> in the data related to the specific publication. At this date, the publication will be:

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

NOTE The revision of this standard will be synchronized with the other parts of the IEC 61158 series.

The list of all the parts of the IEC 61158 series, under the general title *Industrial communication networks – Fieldbus specifications*, can be found on the IEC web site.

INTRODUCTION

This part of IEC 61158 is one of a series produced to facilitate the interconnection of automation system components. It is related to other standards in the set as defined by the “three-layer” fieldbus reference model described in IEC/TR 61158-1.

The application protocol provides the application service by making use of the services available from the data-link or other immediately lower layer. The primary aim of this standard is to provide a set of rules for communication expressed in terms of the procedures to be carried out by peer application entities (AEs) at the time of communication. These rules for communication are intended to provide a sound basis for development in order to serve a variety of purposes:

- as a guide for implementors and designers;
- for use in the testing and procurement of equipment;
- as part of an agreement for the admittance of systems into the open systems environment;
- as a refinement to the understanding of time-critical communications within OSI.

This standard is concerned, in particular, with the communication and interworking of sensors, effectors and other automation devices. By using this standard together with other standards positioned within the OSI or fieldbus reference models, otherwise incompatible systems may work together in any combination.

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 5-12: Application layer protocol specification – Type 12 elements

1 Scope

1.1 General

The fieldbus Application Layer (FAL) provides user programs with a means to access the fieldbus communication environment. In this respect, the FAL can be viewed as a “window between corresponding application programs.”

This standard provides common elements for basic time-critical and non-time-critical messaging communications between application programs in an automation environment and material specific to Type 12 fieldbus. The term “time-critical” is used to represent the presence of a time-window, within which one or more specified actions are required to be completed with some defined level of certainty. Failure to complete specified actions within the time window risks failure of the applications requesting the actions, with attendant risk to equipment, plant and possibly human life.

This standard defines in an abstract way the externally visible behavior provided by the different Types of the fieldbus Application Layer in terms of

- a) the abstract syntax defining the application layer protocol data units conveyed between communicating application entities,
- b) the transfer syntax defining the application layer protocol data units conveyed between communicating application entities,
- c) the application context state machine defining the application service behavior visible between communicating application entities; and
- d) the application relationship state machines defining the communication behavior visible between communicating application entities; and.

The purpose of this standard is to define the protocol provided to

- 1) define the wire-representation of the service primitives defined in IEC 61158-5-12, and
- 2) define the externally visible behavior associated with their transfer.

This standard specifies the protocol of the IEC fieldbus Application Layer, in conformance with the OSI Basic Reference Model (ISO/IEC 7498) and the OSI Application Layer Structure (ISO/IEC 9545).

FAL services and protocols are provided by FAL application-entities (AE) contained within the application processes. The FAL AE is composed of a set of object-oriented Application Service Elements (ASEs) and a Layer Management Entity (LME) that manages the AE. The ASEs provide communication services that operate on a set of related application process object (APO) classes. One of the FAL ASEs is a management ASE that provides a common set of services for the management of the instances of FAL classes.

Although these services specify, from the perspective of applications, how request and responses are issued and delivered, they do not include a specification of what the requesting and responding applications are to do with them. That is, the behavioral aspects of the applications are not specified; only a definition of what requests and responses they can send/receive is specified. This permits greater flexibility to the FAL users in standardizing such object behavior. In addition to these services, some supporting services are also defined in this standard to provide access to the FAL to control certain aspects of its operation.

1.2 Specifications

The principal objective of this standard is to specify the syntax and behavior of the application layer protocol that conveys the application layer services defined in IEC 61158-5-12.

A secondary objective is to provide migration paths from previously-existing industrial communications protocols. It is this latter objective which gives rise to the diversity of protocols standardized in subparts of IEC 61158-6.

1.3 Conformance

This standard does not specify individual implementations or products, nor does it constrain the implementations of application layer entities within industrial automation systems.

There is no conformance of equipment to the application layer service definition standard. Instead, conformance is achieved through implementation of this application layer protocol specification.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60559, *Binary floating-point arithmetic for microprocessor systems*

IEC 61158-3-12, *Industrial communication networks – Fieldbus specifications – Part 3-12: Data-link layer service definition – Type 12 elements*

IEC 61158-4-12, *Industrial communication networks – Fieldbus specifications – Part 4-12: Data-link layer protocol specification – Type 12 elements*

IEC 61158-5-12, *Industrial communication networks – Fieldbus specifications – Part 5-12: Application layer service definition – Type 12 elements*

ISO/IEC 7498-1, *Information technology – Open Systems Interconnection – Basic Reference Model – Part 1: Naming and addressing*

ISO/IEC 7498-3, *Information technology – Open Systems Interconnection – Basic Reference Model – Part 3: The Basic Model*

ISO/IEC 8802-3, *Information technology – Telecommunications and information exchange between systems - Local and metropolitan area networks – Specific requirements – Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and Physical Layer specifications*

ISO/IEC 9545, *Information technology – Open Systems Interconnection – Application Layer structure*

ISO/IEC 9899, *Programming Languages – C.*

ISO/IEC 10731, *Information technology – Open Systems Interconnection – Basic Reference Model – Conventions for the definition of OSI services*

IEEE 802.1D, 2004, *IEEE Standard for Information technology – Telecommunications and information exchange between systems – IEEE standard for local and metropolitan area*

networks – Common specifications – Media access control (MAC) Bridges; available at <http://www.ieee.org>

IEEE 802.1Q, 1998, *IEEE Standard for Information technology – Telecommunications and information exchange between systems – IEEE standard for Local and metropolitan area networks – Virtual bridged local area networks Bridges*; available at <http://www.ieee.org>

IETF RFC 768, *User Datagram Protocol*; available at <http://www.ietf.org>

IETF RFC 791, *Internet Protocol*; available at <http://www.ietf.org>

IETF RFC 792, *Internet Control Message Protocol*; available at <http://www.ietf.org>