



IEC 62024-1

Edition 2.0 2008-02

INTERNATIONAL STANDARD

**High frequency inductive components – Electrical characteristics and measuring methods –
Part 1: Nanohenry range chip inductor**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

R

ICS 29.100.10

ISBN 2-8318-9631-2

CONTENTS

FOREWORD.....	4
1 Scope.....	6
2 Normative references	6
3 Inductance, Q-factor and impedance	6
3.1 Inductance	6
3.1.1 Measuring circuit	7
3.1.2 Mounting of the inductor to the test fixture	7
3.1.3 Measurement method and calculation.....	9
3.1.4 Notes on measurement.....	9
3.2 Quality factor.....	10
3.2.1 Measurement method	10
3.2.2 Measurement circuit	11
3.2.3 Mounting of the inductor	11
3.2.4 Methods of measurement and calculation	11
3.2.5 Notes on measurement.....	11
3.3 Impedance	11
3.3.1 Measurement method	11
3.3.2 Measurement circuit	11
3.3.3 Measurement method and calculation.....	11
3.3.4 Notes on measurement.....	12
4 Resonance frequency.....	12
4.1 Self-resonance frequency.....	12
4.2 Minimum output method	12
4.2.1 Measurement circuit	12
4.2.2 Mounting the inductor for test	13
4.2.3 Measuring method	13
4.2.4 Note on measurement	14
4.3 Reflection method	14
4.3.1 Measurement circuit	14
4.3.2 Mounting the inductor for test	14
4.3.3 Measurement method	15
4.3.4 Notes on measurement.....	15
4.4 Measurement by analyser.....	16
4.4.1 Measurement by impedance analyser.....	16
4.4.2 Measurement by network analyser.....	16
5 DC resistance.....	16
5.1 Measuring circuit (Bridge method).....	16
5.2 Measuring method and calculation formula.....	17
5.3 Precaution for measurement.....	17
5.4 Measuring temperature.....	18
Annex A (normative) Mounting method for a surface mounting coil	19
Figure 1 – Example of circuit for vector voltage/current method	7
Figure 2 – Fixture A	8

Figure 3 – Fixture B	8
Figure 4 – Short device shape	10
Figure 5 – Example of test circuit for the minimum output method.....	12
Figure 6 – Self-resonance frequency test board (minimum output method)	13
Figure 7 – Example of test circuit for the reflection method	14
Figure 8 – Self-resonance frequency test board (reflection method).....	15
Figure 9 – Suitable test fixture for measuring self-resonance frequency.....	16
Figure 10 – Example of measuring circuit of d.c. resistance	17
Table 1 – Dimensions of l and d	8
Table 2 – Short device dimensions and inductances	10

INTERNATIONAL ELECTROTECHNICAL COMMISSION

HIGH FREQUENCY INDUCTIVE COMPONENTS – ELECTRICAL CHARACTERISTICS AND MEASURING METHODS –

Part 1: Nanohenry range chip inductor

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62024-1 has been prepared by IEC technical committee 51: Magnetic components and ferrite materials.

This second edition cancels and replaces the first edition published in 2002. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) sizes 0402 added in Table 1 and Table 2;
- b) contents of 4.4 reviewed for easier understanding;
- c) correct errors in 3.1.4.2.

The text of this standard is based on the following documents:

FDIS	Report on voting
51/908/FDIS	51/915/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of IEC 62024 series, published under the general title *High frequency inductive components – Electrical characteristics and measuring methods*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

The contents of the corrigendum of July 2008 have been included in this copy.

HIGH FREQUENCY INDUCTIVE COMPONENTS – ELECTRICAL CHARACTERISTICS AND MEASURING METHODS –

Part 1: Nanohenry range chip inductor

1 Scope

This part of IEC 62024 specifies electrical characteristics and measuring methods for the nanohenry range chip inductor that is normally used in high frequency (over 100 kHz) range.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61249-2-7, *Materials for printed boards and other interconnecting structures – Part 2-7: Reinforced base materials clad and unclad – Epoxide woven E-glass laminated sheet of defined flammability (vertical burning test) copper-clad*

ISO 6353-3, *Reagents for chemical analysis – Part 3: Specifications – Second series*

ISO 9453, *Soft solder alloys – Chemical compositions and forms*