

# JIS

JAPANESE  
INDUSTRIAL  
STANDARD

Translated and Published by  
Japanese Standards Association

---

---

**JIS B 8839** : 2014

(JCA/JSA)

**Graphic symbols for gondola control**

---

ICS 01.080.20

Reference number : JIS B 8839 : 2014 (E)

PROTECTED BY COPYRIGHT

6 5

B 8839 : 2014

Date of Establishment: 2014-01-25

Date of Public Notice in Official Gazette: 2014-01-27

Investigated by: Japanese Industrial Standards Committee  
Standards Board

Technical Committee on Longistics and Distribution of  
Goods

---

JIS B 8839 : 2014, First English edition published in 2014-10

Translated and published by: Japanese Standards Association  
Mita MT Building, 3-13-12, Mita, Minato-ku, Tokyo, 108-0073 JAPAN

---

In the event of any doubts arising as to the contents,  
the original JIS is to be the final authority.

© JSA 2014

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

HT/HN

PROTECTED BY COPYRIGHT

**Contents**

	Page
1 Scope .....	1
2 Terms and definitions .....	1
3 Marking of controls .....	2
3.1 Marking of gondola controls (switches) .....	2
3.2 Marking method .....	2
3.3 Marking of operational directions and the like of special working devices .....	2
3.4 Letters and graphic symbols for marking .....	3

## Foreword

This translation has been made based on the original Japanese Industrial Standard established by the Minister of Health, Labour and Welfare and the Minister of Economy Trade and Industry through deliberations at the Japanese Industrial Standards Committee according to the proposal for establishment of Japanese Industrial Standard submitted by Japan Crane Association (JCA)/Japanese Standards Association (JSA) with the draft prepared from the association standard (Japan Crane Association Standard : **JCAS5003-2011**) being attached, based on the provision of Article 12 Clause 1 of the Industrial Standardization Law.

This **JIS** document is protected by the Copyright Law.

Attention is drawn to the possibility that some parts of this Standard may conflict with patent rights, applications for a patent after opening to the public or utility model rights. The relevant Ministers and the Japanese Industrial Standards Committee are not responsible for identifying any of such patent rights, applications for a patent after opening to the public or utility model rights.

## Graphic symbols for gondola control

### 1 Scope

This Japanese Industrial Standard specifies the letters, graphic symbols and their markings to be given on gondolas for such operations as building cleaning, building painting and welding, for the purpose of preventing accidents caused by incorrect gondola operations.

### 2 Terms and definitions

For the purpose of this Standard, the following terms and definitions apply.

#### 2.1 gondola

device comprised of a hanging scaffold, a lift and other equipment and auxiliaries where the hanging scaffold work floor is designed to be lifted or lowered by a dedicated lift (see figure 1)

The control panel of the work floor is, in many cases, fitted toward the counter-wall side.

#### 2.2 work floor

floor which is provided to bring workers close to a work location and to enable the workers to carry out such operations as cleaning, painting and welding in high places

The floor materials are closely spaced and firmly secured to the frame, and hand rails and toeboards are provided.

#### 2.3 carriage

equipment in a gondola which is placed on the rooftop and mounted with a lift, a travelling equipment, an arm-elevating equipment, a control panel, and so on (see figure 1)

#### 2.4 arm

pillar structure which extends from the carriage and moves with variable angles and supports the work floor using wire ropes and other means (see figure 1)

#### 2.5 base turning

turning of the carriage or the arm (see figure 1)

It is also referred to as carriage turning.

#### 2.6 turning at the arm tip

turning of the work floor with the centre of turn at the arm tip (see figure 1)