

BS 8541-6:2015



BSI Standards Publication

**Library objects for architecture,
engineering and construction –**
Part 6: Product and facility declarations –
Code of practice

bsi.

...making excellence a habit.™

Publishing and copyright information

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2015
Published by BSI Standards Limited 2015

ISBN 978 0 580 85281 7

ICS 03.100.50

The following BSI references relate to the work on this document:

Committee reference B/555

Draft for comment 14/30294759 DC

Publication history

First published, March 2015

Amendments issued since publication

Date	Text affected
------	---------------

Contents

Foreword *ii*

1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Declaration processes	2
5	Principles for the exchange of declarations	3

Annexes

Annex A (informative)	Example product declaration schemes	11
Annex B (informative)	Product declaration attributes	29

Bibliography 33

List of figures

Figure 1	– Core maturity model	<i>iii</i>
Figure 2	– Construction object	3
Figure 3	– Declaration property set	4

List of tables

Table 1	– Quantity set definition	3
Table 2	– Quantity definitions	4
Table 3	– Property set naming	4
Table 4	– Description	5
Table 5	– Properties used for product declaration identification	6
Table 6	– Declaration values for a property [Property]	8
Table 7	– Scenario properties	9
Table 8	– Regional (for facilities) and date basis	10
Table 9a	– Expected declaration properties within construction library objects	10
Table 9b	– Expected declaration properties for facilities	10
Table A.1	– Environmental product declaration property set definition	11
Table A.2	– Environmental property definitions	12
Table A.3	– Example transport scenario properties	15
Table A.4	– BRE property set definition	16
Table A.5	– BRE property definitions	17
Table A.6	– Carbon data property set definition	19
Table A.7	– Carbon data property definitions	19
Table A.8	– Thermal property set definition	20
Table A.9	– Thermal property definitions	20
Table A.10	– Construction property Set definition	20
Table A.11	– Construction property definitions	21
Table A.12	– WRAP property set definition	23
Table A.13	– WRAP property definitions	23
Table A.14	– WRAP property set definition – indicative economic impacts	23
Table A.15	– WRAP property definitions – indicative economic impacts	24
Table A.16	– WRAP property set definition – environmental impacts	24
Table A.17	– WRAP property definitions – environmental impacts	24
Table A.18	– WRAP property set definition	24
Table A.19	– WRAP property definitions	25
Table A.20	– DEC property set definition	27
Table A.21	– DEC property definitions	28
Table A.22	– Service life declaration definitions	29
Table B.1	– Attribute	30

Summary of pages

This document comprises a front cover, an inside front cover, pages i to iv, pages 1 to 34, an inside back cover and a back cover.

Foreword

Publishing information

This part of BS 8541 is published by BSI Standards Limited, under licence from The British Standards Institution, and came into effect on 31 March 2015. It was prepared by Technical Committee B/555, *Construction design, modelling and data exchange*. A list of organizations represented on this committee can be obtained on request to its secretary.

Relationship with other publications

BS 8541 comprises six parts as follows:


- Part 1, *Identification and classification*
- Part 2, *Recommended 2D symbols of building elements for use in building information modelling*
- Part 3, *Shape and measurement*
- Part 4, *Attributes for specification and assessment*
- Part 5, *Assemblies*
- Part 6 (this part), *Product and facility declarations*

BS 8541-1, BS 8541-3 and BS 8541-4 document best practice for the development and application of construction library objects to support Building Information Modelling (BIM) based design, standardization, specification and construction processes. See BS 8541-1 and Figure 1.

BS 8541-2 documents best practice for the use of 2D symbols for construction objects. BS 8541-5 and BS 8541-6 document best practice for the transmission of assemblies of construction objects and for the transmission of formal performance declarations of products and facilities.

The IFC standard (BS ISO 16739) includes recommendations for the association of base quantities and geometry for objects. The use of the IFC standard can be supplemented by using UK specific recommendations, such as are published by buildingSMART UK on behalf of RIBAE NBS under its UK national BIM Library initiative. For further information on work within ISO, see BS 8541-1.

Figure 1 Core maturity model



Use of this document

As a code of practice, this part of BS 8541 takes the form of guidance and recommendations. It should not be quoted as if it were a specification and particular care should be taken to ensure that claims of compliance are not misleading.

Any user claiming compliance with this part of BS 8541 is expected to be able to justify any course of action that deviates from its recommendations.

Presentational conventions

The provisions in this standard are presented in roman (i.e. upright) type. Its recommendations are expressed in sentences in which the principal auxiliary verb is "should".

Commentary, explanation and general informative material is presented in smaller italic type, and does not constitute a normative element.

¹⁾ <http://shop.bsigroup.com/bim> [viewed: 24-3-2015]

The word “should” is used to express recommendations of this standard. The word “may” is used in the text to express permissibility, e.g. as an alternative to the primary recommendation of the clause. The word “can” is used to express possibility, e.g. a consequence of an action or an event.

Notes and commentaries are provided throughout the text of this standard. Notes give references and additional information that are important but do not form part of the recommendations. Commentaries give background information.

Contractual and legal considerations

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

1 Scope

This part of BS 8541 gives recommendations on the transmission of product declarations relating to construction library objects and facility declarations (including buildings, infrastructure and built assets). It applies primarily to manufacturers' specific products, but the principles and some examples are also applicable to facility declarations.

NOTE 1 Independent declarations are an increasingly important aspect of product and facility data, covering environmental and other performance.

This part of BS 8541 gives recommendations on conveying declarations as part of a standard product data set (supplementary to printed labels, annexes and document lodgement) and integrates product and facility declarations into information-driven design, construction and operational processes.

This part of BS 8541 is applicable to any independent declaration scheme and establishes principles for the identification of declarations and their origin. It defines the level of information appropriate for specific uses including confirmation, reporting, and analysis. The intent is to allow any declaration to be communicated with indications as to the degree of attestation offered. The specific values declared are given in the context of a specific declaration scheme and supported with details of the relevant life cycle stage and details of its scenario.

NOTE 2 Construction products regulations and CEN standards for buildings and products provide the primary examples. This part of BS 8541 supports the communication of the voluntary environmental product declarations (EPDs) required by BS EN 15804 and BS EN 15978, as well as the CE marking details, in a format which can be incorporated in Building Information Modelling (BIM) processes. It also covers the communication of other product declarations such as wastage rates developed with the UK Government WRAP programme and UK government display energy certificate (DEC) declaration scheme.

NOTE 3 COBie, BS ISO 16739 IFC and IFCXML are used as example formats with reference to BS ISO 10303-21 and ISO/TS 10303-28. These formats can be mapped to standard printed forms if required.

NOTE 4 In situations where the adoption of data-driven design is partial or incomplete, this part of BS 8541 gives further recommendations. If a particular project is formally committed to integrated working then this standard may be adopted as a requirement.

NOTE 5 Self-declared environmental claims (such as described as Type II environmental labels in BS EN ISO 14021) have the lowest degree of attestation but are also covered by this standard.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

BS 8541-1, *Library objects for architecture, engineering and construction – Part 1: Identification and classification – Code of practice*

BS 8541-2, *Library objects for architecture, engineering and construction – Part 2: Recommended 2D symbols of building elements for use in building information modelling*

BS 8541-3, *Library objects for architecture, engineering and construction – Part 3: Shape and measurement – Code of practice*