

JIS

JAPANESE
INDUSTRIAL
STANDARD

Translated and Published by
Japanese Standards Association

JIS K 5600-2-3 : 2014

(JPMA/JSA)

**Testing methods for paints—
Part 2: Characteristics and stability
of paints—Section 3: Viscosity
(Cone and plate methods)**

ICS 87.040

Reference number : **JIS K 5600-2-3 : 2014 (E)**

K 5600-2-3 : 2014

Date of Establishment: 1999-04-20

Date of Revision: 2014-03-20

Date of Public Notice in Official Gazette: 2014-03-20

Investigated by: Japanese Industrial Standards Committee
Standards Board

Technical Committee on Chemical Products

JIS K 5600-2-3:2014, First English edition published in 2016-05

Translated and published by: Japanese Standards Association
Mita MT Building, 3-13-12, Mita, Minato-ku, Tokyo, 108-0073 JAPAN

In the event of any doubts arising as to the contents,
the original JIS is to be the final authority.

© JSA 2016

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

NH/AT

PROTECTED BY COPYRIGHT

Contents

	Page
Introduction.....	1
1 Scope.....	1
2 Normative references	1
3 Terms and definitions	2
4 Viscometer	2
5 Sampling.....	2
6 Checking the apparatus	2
7 Checking the temperature control	3
8 Procedure	3
9 Cleaning the apparatus	3
10 Precision	3
11 Test report	3
Annex A (informative) Cone-and-plate viscometers	5
Annex JA (informative) Comparison table between JIS and corresponding International Standard	7

Foreword

This translation has been made based on the original Japanese Industrial Standard revised by the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee as the result of proposal for revision of Japanese Industrial Standard submitted by Japan Paint Manufacturers Association (JPMA)/Japanese Standards Association (JSA) with the draft being attached, based on the provision of Article 12 Clause 1 of the Industrial Standardization Law applicable to the case of revision by the provision of Article 14.

Consequently **JIS K 5600-2-3:1999** is replaced with this Standard.

This **JIS** document is protected by the Copyright Law.

Attention is drawn to the possibility that some parts of this Standard may conflict with patent rights, applications for a patent after opening to the public or utility model rights. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying any of such patent rights, applications for a patent after opening to the public or utility model rights.

JIS K 5600-2 series consists of the following 7 parts under the general title “*Testing methods for paints—Part 2: Characteristics and stability of paints*”:

Section 1: Colour number (Visual method)

Section 2: Viscosity

Section 3: Viscosity (Cone and plate methods)

Section 4: Density (Pyknometer method)

Section 5: Fineness of grind

Section 6: Pot life

Section 7: Storage stability

Testing methods for paints— Part 2: Characteristics and stability of paints—Section 3: Viscosity (Cone and plate methods)

Introduction

This Japanese Industrial Standard has been prepared based on the first edition of **ISO 2884-1** published in 1999 with some additions of specifications as well as modifications of the technical contents.

The portions given dotted underlines are the matters in which the contents of the corresponding International Standard have been modified. A list of modifications with the explanations is given in Annex JA.

1 Scope

This Standard specifies the general procedure to be followed in determining the dynamic viscosity of paints, varnishes and related products at a rate of shear not less than $9\,000\text{ s}^{-1}$ and not higher than $12\,000\text{ s}^{-1}$.

This Standard supplements **JIS K 5600-2-2**.

NOTE 1 The value obtained gives information about the resistance offered by the material to brushing, spraying and roller coating during application. The method specified in this Standard is suitable for all paints and varnishes whether they are Newtonian in behaviour or not. Materials containing dispersions of large particles will produce spurious results.

NOTE 2 The International Standard corresponding to this Standard and the symbol of degree of correspondence are as follows.

ISO 2884-1:1999 *Paints and varnishes—Determination of viscosity using rotary viscometers—Part 1: Cone-and-plate viscometer operated at a high rate of shear* (MOD)

In addition, symbols which denote the degree of correspondence in the contents between the relevant International Standard and **JIS** are IDT (identical), MOD (modified), and NEQ (not equivalent) according to **ISO/IEC Guide 21-1**.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this Standard. The most recent editions of the standards (including amendments) indicated below shall be applied.

JIS K 5500 *Glossary of terms for coating materials*

JIS K 5600-1-2 *Testing methods for paints—Part 1: General rules—Section 2: Sampling*

NOTE : Corresponding International standard: ISO 15528 *Paints, varnishes and raw materials for paints and varnishes—Sampling* (IDT)