

INTERNATIONAL STANDARD



**Universal serial bus interfaces for data and power –
Part 1-2: Common components – USB Power Delivery specification**



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2016 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.



IEC 62680-1-2

Edition 1.0 2016-11

INTERNATIONAL STANDARD



**Universal serial bus interfaces for data and power –
Part 1-2: Common components – USB Power Delivery specification**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 29.220; 33.120; 35.200

ISBN 978-2-8322-3710-6

Warning! Make sure that you obtained this publication from an authorized distributor.

INTERNATIONAL ELECTROTECHNICAL COMMISSION

UNIVERSAL SERIAL BUS INTERFACES FOR DATA AND POWER

Part 1-2: Common components – USB Power Delivery specification

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62680-1-2 has been prepared by technical area 14: Interfaces and methods of measurement for personal computing equipment, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

The text of this standard was prepared by the USB Implementers Forum (USB-IF). The structure and editorial rules used in this publication reflect the practice of the organization which submitted it.

The text of this standard is based on the following documents:

CDV	Report on voting
100/2728/CDV	100/2729/RVC

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

A list of all parts in the IEC 62680 series, published under the general title *Universal serial bus interfaces for data and power*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

The IEC 62680 series is based on a series of specifications that were originally developed by the USB Implementers Forum (USB-IF). These specifications were submitted to the IEC under the auspices of a special agreement between the IEC and the USB-IF.

This standard is the USB-IF publication USB Power Delivery Specification Revision 3.0 V.1.0.

The USB Implementers Forum, Inc.(USB-IF) is a non-profit corporation founded by the group of companies that developed the Universal Serial Bus specification. The USB-IF was formed to provide a support organization and forum for the advancement and adoption of Universal Serial Bus technology. The Forum facilitates the development of high-quality compatible USB peripherals (devices), and promotes the benefits of USB and the quality of products that have passed compliance testing.

ANY USB SPECIFICATIONS ARE PROVIDED TO YOU "AS IS, "WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY, NON-INFRINGEMENT, OR FITNESS FOR ANY PARTICULAR PURPOSE. THE USB IMPLEMENTERS FORUM AND THE AUTHORS OF ANY USB SPECIFICATIONS DISCLAIM ALL LIABILITY, INCLUDING LIABILITY FOR INFRINGEMENT OF ANY PROPRIETARY RIGHTS, RELATING TO USE OR IMPLEMENTATION OR INFORMATION IN THIS SPECIFICATION.

THE PROVISION OF ANY USB SPECIFICATIONS TO YOU DOES NOT PROVIDE YOU WITH ANY LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS.

Entering into USB Adopters Agreements may, however, allow a signing company to participate in a reciprocal, RAND-Z licensing arrangement for compliant products. For more information, please see:

<http://www.usb.org/developers/docs/>

http://www.usb.org/developers/devclass_docs#approved

IEC DOES NOT TAKE ANY POSITION AS TO WHETHER IT IS ADVISABLE FOR YOU TO ENTER INTO ANY USB ADOPTERS AGREEMENTS OR TO PARTICIPATE IN THE USB IMPLEMENTERS FORUM.”

Universal Serial Bus Power Delivery Specification

Revision 3.0, V1.0. 11 December 2015

Editors

Bob Dunstan	Intel Corporation
Richard Petrie	DisplayLink

Contributors

Charles Wang	ACON, Advanced-Connectek, Inc.
Conrad Choy	ACON, Advanced-Connectek, Inc.
Steve Sedio	ACON, Advanced-Connectek, Inc.
Vicky Chuang	ACON, Advanced-Connectek, Inc.
Joseph Scanlon	Advanced Micro Devices
Howard Chang	Allion Labs, Inc.
Greg Stewart	Analogix Semiconductor, Inc.
Mehran Badii	Analogix Semiconductor, Inc.
Bill Cornelius	Apple
Colin Whitby-Strevens	Apple
Corey Axelowitz	Apple
Corey Lange	Apple
Dave Conroy	Apple
David Sekowski	Apple
Girault Jones	Apple
James Orr	Apple
Jason Chung	Apple
Jennifer Tsai	Apple
Karl Bowers	Apple
Keith Porthouse	Apple
Matt Mora	Apple
Paul Baker	Apple
Reese Schreiber	Apple
Sameer Kelkar	Apple
Sasha Tietz	Apple
Sree Raman	Apple
William Ferry	Apple
Zaki Moussaoui	Apple
Bernard Shyu	Bizlink Technology, Inc.
Eric Wu	Bizlink Technology, Inc.
Morphy Hsieh	Bizlink Technology, Inc.
Shawn Meng	Bizlink Technology Inc.
Tiffany Hsiao	Bizlink Technology, Inc.
Weichung Ooi	Bizlink Technology, Inc.
Michal Staworko	Cadence Design Systems, Inc.
Alessandro Ingrassia	Canova Tech
Andrea Colognese	Canova Tech
Davide Ghedin	Canova Tech
Matteo Casalin	Canova Tech
Nicola Scantamburlo	Canova Tech

Yi-Feng Lin	Canyon Semiconductor	
Anup Nayak	Cypress Semiconductor	
Jagadeesan Raj	Cypress Semiconductor	
Pradeep Bajpai	Cypress Semiconductor	
Rushil Kadakia	Cypress Semiconductor	
Steven Wong	Cypress Semiconductor	
Subu Sankaran	Cypress Semiconductor	
Sumeet Gupta	Cypress Semiconductor	
Adolfo Montero	Dell Inc.	
Bruce Montag	Dell Inc.	
Gary Verdun	Dell Inc.	
Merle Wood	Dell Inc.	
Mohammed Hijazi	Dell Inc.	
Siddhartha Reddy	Dell Inc.	
Dan Ellis	DisplayLink	
Jason Young	DisplayLink	
Peter Burgers	DisplayLink	
Richard Petrie	DisplayLink	PD Chair/Device Policy Lead
Abel Astley	Ellisys	
Chuck Trefts	Ellisys	
Emmanuel Durin	Ellisys	
Mario Pasquali	Ellisys	
Chien-Cheng Kuo	Etron Technology, Inc.	
Jack Yang	Etron Technology, Inc.	
Richard Crisp	Etron Technology, Inc.	
Shyanjia Chen	Etron Technology, Inc.	
TsungTa Lu	Etron Technology, Inc.	
Christian Klein	Fairchild Semiconductor	
Oscar Freitas	Fairchild Semiconductor	
Souhib Harb	Fairchild Semiconductor	
AJ Yang	Foxconn / Hon Hai	
Fred Fons	Foxconn / Hon Hai	
Steve Sedio	Foxconn / Hon Hai	
Terry Little	Foxconn / Hon Hai	
Bob McVay	Fresco Logic Inc.	
Christopher Meyers	Fresco Logic Inc.	
Tom Burton	Fresco Logic Inc.	
Dian Kurniawan	Fresco Logic Inc.	
Adam Rodriguez	Google Inc.	
Alec Berg	Google Inc.	
David Schneider	Google Inc.	
Jim Guerin	Google Inc.	
Juan Fantin	Google Inc.	
Ken Wu	Google Inc.	
Mark Hayter	Google Inc.	
Nithya Jagannathan	Google Inc.	

Todd Broch	Google Inc.	
Vincent Palatin	Google Inc.	
Mike Engbretson	Granite River Labs	
Rajaraman V	Granite River Labs	
Alan Berkema	Hewlett Packard	
Lee Atkinson	Hewlett Packard	
Rahul Lakdawala	Hewlett Packard	
Robin Castell	Hewlett Packard	
Roger Benson	Hewlett Packard	
Ron Schooley	Hewlett Packard	
Vaibhav Malik	Hewlett Packard	
Walter Fry	Hewlett Packard	
Bob Dunstan	Intel Corporation	PD Chair/Protocol WG Lead
Brad Saunders	Intel Corporation	
Chee Lim Nge	Intel Corporation	
Christine Krause	Intel Corporation	
Dan Froelich	Intel Corporation	
David Harriman	Intel Corporation	
David Hines	Intel Corporation	
David Thompson	Intel Corporation	
Guobin Liu	Intel Corporation	
Harry Skinner	Intel Corporation	
Henrik Leegaard	Intel Corporation	
Jervis Lin	Intel Corporation	
John Howard	Intel Corporation	
Karthi Vadivelu	Intel Corporation	
Leo Heiland	Intel Corporation	
Maarit Harkonen	Intel Corporation	
Nge Chee Lim	Intel Corporation	
Paul Durley	Intel Corporation	
Rahman Ismail	Intel Corporation	System Policy Lead
Ronald Swartz	Intel Corporation	
Sarah Sharp	Intel Corporation	
Scott Brenden	Intel Corporation	
Sridharan Ranganathan	Intel Corporation	
Steve McGowan	Intel Corporation	
Tim McKee	Intel Corporation	PD Chair/Compliance Lead
Toby Opferman	Intel Corporation	
Kenta Minejima	Japan Aviation Electronics Industry Ltd. (JAE)	
Mark Saubert	Japan Aviation Electronics Industry Ltd. (JAE)	
Toshio Shimoyama	Japan Aviation Electronics Industry Ltd. (JAE)	
Brian Fetz	Keysight Technologies Inc.	
Babu Mailachalam	Lattice Semiconductor Corp	
Gianluca Mariani	Lattice Semiconductor Corp	
Joel Coplen	Lattice Semiconductor Corp	

Thomas Watza	Lattice Semiconductor Corp
Vesa Lauri	Lattice Semiconductor Corp
Daniel H Jacobs	LeCroy Corporation
Jake Jacobs	LeCroy Corporation
Kimberley McKay	LeCroy Corporation
Mike Micheletti	LeCroy Corporation
Roy Chestnut	LeCroy Corporation
Phil Jakes	Lenovo
Dave Thompson	LSI Corporation
Alan Kinningham	Luxshare-ICT
Daniel Chen	Luxshare-ICT
Josue Castillo	Luxshare-ICT
Chris Yokum	MCCI Corporation
Geert Knapen	MCCI Corporation
Terry Moore	MCCI Corporation
Velmurugan Selvaraj	MCCI Corporation
Brian Marley	Microchip Technology Inc.
Dave Perchlik	Microchip Technology Inc.
Don Perkins	Microchip Technology Inc.
John Sisto	Microchip Technology Inc.
Josh Averyt	Microchip Technology Inc.
Kiet Tran	Microchip Technology Inc.
Mark Bohm	Microchip Technology Inc.
Matthew Kalibat	Microchip Technology Inc.
Mick Davis	Microchip Technology Inc.
Rich Wahler	Microchip Technology Inc.
Ronald Kunin	Microchip Technology Inc.
Shannon Cash	Microchip Technology Inc.
Anthony Chen	Microsoft Corporation
Dave Perchlik	Microsoft Corporation
David Voth	Microsoft Corporation
Geoff Shew	Microsoft Corporation
Jayson Kastens	Microsoft Corporation
Kai Inha	Microsoft Corporation
Marwan Kadado	Microsoft Corporation
Rahul Ramadas	Microsoft Corporation
Randy Aull	Microsoft Corporation
Shiu Ng	Microsoft Corporation
Timo Toivola	Microsoft Corporation
Toby Nixon	Microsoft Corporation
Vivek Gupta	Microsoft Corporation
Yang You	Microsoft Corporation
Dan Wagner	Motorola Mobility Inc.
Ben Crowe	MQP Electronics Ltd.
Pat Crowe	MQP Electronics Ltd.
Sten Carlsen	MQP Electronics Ltd.

Frank Borngräber	Nokia Corporation	
Kai Inha	Nokia Corporation	
Pekka Leinonen	Nokia Corporation	
Richard Petrie	Nokia Corporation	PD Vice-Chair/Device Policy Lead
Sten Carlsen	Nokia Corporation	Physical Layer WG Lead
Abhijeet Kulkarni	NXP Semiconductors	
Ahmad Yazdi	NXP Semiconductors	
Bart Vertenten	NXP Semiconductors	
Dong Nguyen	NXP Semiconductors	
Guru Prasad	NXP Semiconductors	
Ken Jaramillo	NXP Semiconductors	
Krishnan TN	NXP Semiconductors	
Michael Joehren	NXP Semiconductors	
Robert de Nie	NXP Semiconductors	
Rod Whitby	NXP Semiconductors	
Vijendra Kuroodi	NXP Semiconductors	
Robert Heaton	Obsidian Technology	
Bryan McCoy	ON Semiconductor	
Cor Voorwinden	ON Semiconductor	
Edward Berrios	ON Semiconductor	Power Supply WG Lead
Tom Duffy	ON Semiconductor	
Craig Wiley	Parade Technologies Inc.	
Ricardo Pregiteer	Power Integrations	
Chris Sporck	Qualcomm, Inc.	
Craig Aiken	Qualcomm, Inc.	
George Paparrizos	Qualcomm, Inc	
Giovanni Garcea	Qualcomm, Inc	
James Goel	Qualcomm, Inc	
Joshua Warner	Qualcomm, Inc	
Narendra Mehta	Qualcomm, Inc.	
Terry Remple	Qualcomm, Inc.	
Yoram Rimoni	Qualcomm, Inc.	
Atsushi Mitamura	Renesas Electronics Corp.	
Dan Aoki	Renesas Electronics Corp.	
Kiichi Muto	Renesas Electronics Corp.	
Masami Katagiri	Renesas Electronics Corp.	
Nobuo Furuya	Renesas Electronics Corp.	
Patrick Yu	Renesas Electronics Corp.	
Peter Teng	Renesas Electronics Corp.	
Philip Leung	Renesas Electronics Corp.	
Steve Roux	Renesas Electronics Corp.	
Tetsu Sato	Renesas Electronics Corp.	
Heinz Wei	Richtek Technology Corporation	
Tatsuya Irisawa	Ricoh Company Ltd.	
Akihiro Ono	Rohm Co. Ltd.	
Chris Lin	Rohm Co. Ltd.	

Hidenori Nishimoto	Rohm Co. Ltd.	
Kris Bahar	Rohm Co. Ltd.	
Manabu Miyata	Rohm Co. Ltd.	
Ruben Balbuena	Rohm Co. Ltd.	
Takashi Sato	Rohm Co. Ltd.	
Vijendra Kuroodi	Rohm Co. Ltd.	
Yusuke Kondo	Rohm Co. Ltd.	
Matti Kulmala	Salcomp Plc	
Toni Lehimo	Salcomp Plc	
Tong Kim	Samsung Electronics Co. Ltd.	
Alvin Cox	Seagate Technology LLC	Cab Con WG Lead
John Hein	Seagate Technology LLC	
Marc Noblitt	Seagate Technology LLC	
Ronald Rueckert	Seagate Technology LLC	
Tony Priborsky	Seagate Technology LLC	
John Sisto	SMSC	
Ken Gay	SMSC	
Mark Bohm	SMSC	
Richard Wahler	SMSC	
Shannon Cash	SMSC	
Tim Knowlton	SMSC	
William Chiechi	SMSC	
Fabien Friess	ST-Ericsson	
Giuseppe Platania	ST-Ericsson	
Jean-Francois Gatto	ST-Ericsson	
Milan Stamenkovic	ST-Ericsson	
Nicolas Florenchie	ST-Ericsson	
Patrizia Milazzo	ST-Ericsson	
Christophe Lorin	ST-Microelectronics	
John Bloomfield	ST-Microelectronics	
Massimo Panzica	ST-Microelectronics	
Meriem Mersel	ST-Microelectronics	
Nathalie Ballot	ST-Microelectronics	
Pascal Legrand	ST-Microelectronics	
Patrizia Milazzo	ST-Microelectronics	
Zongyao Wen	Synopsys, Inc.	
Joan Marrinan	Tektronix	
Kimberley McKay	Teledyne-LeCroy	
Matthew Dunn	Teledyne-LeCroy	
Tony Minchell	Teledyne-LeCroy	
Anand Dabak	Texas Instruments	
Bill Waters	Texas Instruments	
Deric Waters	Texas Instruments	Physical Layer WG Lead
Grant Ley	Texas Instruments	
Ingolf Frank	Texas Instruments	
Ivo Huber	Texas Instruments	

Javed Ahmad	Texas Instruments
Jean Picard	Texas Instruments
Martin Patoka	Texas Instruments
Scott Jackson	Texas Instruments
Srinath Hosur	Texas Instruments
Steven Tom	Texas Instruments
Dydron Lin	VIA Technologies, Inc.
Fong-Jim Wang	VIA Technologies, Inc.
Jay Tseng	VIA Technologies, Inc.
Rex Chang	VIA Technologies, Inc.
Terrance Shih	VIA Technologies, Inc.
Charles Neumann	Western Digital Technologies, Inc.
Curtis Stevens	Western Digital Technologies, Inc.
John Maroney	Western Digital Technologies, Inc.

Revision History

Revision	Version	Comments	Issue Date
1.0	1.0	Initial release Revision 1.0	5 July, 2012
1.0	1.1	Including errata through 31-October-2012	31 October 2012
1.0	1.2	Including errata through 26-June-2013	26 June, 2013
1.0	1.3	Including errata through 11-March-2014	11 March 2014
2.0	1.0	Initial release Revision 2.0	11 August 2014
2.0	1.1	Including errata through 7-May 2015	7 May 2015
3.0	1.0	Initial release Revision 3.0	11 December 2015

INTELLECTUAL PROPERTY DISCLAIMER

THIS SPECIFICATION IS PROVIDED TO YOU "AS IS" WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY, NON-INFRINGEMENT, OR FITNESS FOR ANY PARTICULAR PURPOSE. THE AUTHORS OF THIS SPECIFICATION DISCLAIM ALL LIABILITY, INCLUDING LIABILITY FOR INFRINGEMENT OF ANY PROPRIETARY RIGHTS, RELATING TO USE OR IMPLEMENTATION OF INFORMATION IN THIS SPECIFICATION. THE PROVISION OF THIS SPECIFICATION TO YOU DOES NOT PROVIDE YOU WITH ANY LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS.

Please send comments via electronic mail to techsup@usb.org

For industry information, refer to the USB Implementers Forum web page at <http://www.usb.org>

All product names are trademarks, registered trademarks, or service marks of their respective owners.

Copyright © 2010-2015 Hewlett-Packard Company, Intel Corporation, LSI Corporation, Microsoft Corporation, Renesas, STMicroelectronics, and Texas Instruments

All rights reserved.

Table of Contents

FOREWORD.....	2
INTRODUCTION.....	4
Contributors.....	6
Revision History.....	12
Table of Contents	13
List of Tables	18
List of Figures.....	22
1 Introduction	29
1.1 Overview	29
1.2 Purpose.....	30
1.3 Scope	30
1.4 Conventions.....	31
1.4.1 Precedence	31
1.4.2 Keywords	31
1.4.3 Numbering.....	32
1.5 Related Documents.....	32
1.6 Terms and Abbreviations	33
1.7 Parameter Values	39
2 Overview	39
2.1 Introduction.....	39
2.2 Section Overview.....	40
2.3 USB Power Delivery Capable Devices	41
2.4 SOP* Communication	42
2.4.1 Introduction	42
2.4.2 SOP* Collision Avoidance.....	42
2.4.3 SOP Communication	43
2.4.4 SOP*/SOP'' Communication with Cable Plugs.....	43
2.5 Operational Overview	44
2.5.1 Source Operation	44
2.5.2 Sink Operation.....	46
2.5.3 Cable Plugs.....	48
2.6 Architectural Overview	49
2.6.1 Policy	51
2.6.2 Message Formation and Transmission.....	52
2.6.3 Collision Avoidance	52
2.6.4 Power supply.....	53
2.6.5 DFP/UFP	53
2.6.6 VCONN Source	54
2.6.7 Cable and Connectors	54
2.6.8 Interactions between Non-PD, BC and PD devices	54
2.6.9 Power Rules	54
3 USB Type-A and USB Type-B Cable Assemblies and Connectors	54
4 Electrical Requirements.....	54
4.1 Interoperability with other USB Specifications	54
4.2 Dead Battery Detection / Unpowered Port Detection	55
4.3 Cable IR Ground Drop (IR Drop).....	55

- 4.4 Cable Type Detection 55
- 5 Physical Layer 55
 - 5.1 Physical Layer Overview 55
 - 5.2 Physical Layer Functions 56
 - 5.3 Symbol Encoding 56
 - 5.4 Ordered Sets 57
 - 5.5 Transmitted Bit Ordering 59
 - 5.6 Packet Format 59
 - 5.6.1 Packet Framing 60
 - 5.6.2 CRC 62
 - 5.6.3 Packet Detection Errors 64
 - 5.6.4 Hard Reset 65
 - 5.6.5 Cable Reset 65
 - 5.7 Collision Avoidance 66
 - 5.8 Biphase Mark Coding (BMC) Signaling Scheme 67
 - 5.8.1 Encoding and signaling 67
 - 5.8.2 Transmit and Receive Masks 71
 - 5.8.3 Transmitter Load Model 78
 - 5.8.4 BMC Common specifications 79
 - 5.8.5 BMC Transmitter Specifications 80
 - 5.8.6 BMC Receiver Specifications 84
 - 5.9 Built in Self-Test (BIST) 86
 - 5.9.1 BIST Carrier Mode 86
 - 5.9.2 BIST Test Data 86
- 6 Protocol Layer 87
 - 6.1 Overview 87
 - 6.2 Messages 87
 - 6.2.1 Message Construction 88
 - 6.3 Control Message 94
 - 6.3.1 GoodCRC Message 95
 - 6.3.2 GotoMin Message 96
 - 6.3.3 Accept Message 96
 - 6.3.4 Reject Message 96
 - 6.3.5 Ping Message 97
 - 6.3.6 PS_RDY Message 97
 - 6.3.7 Get_Source_Cap Message 97
 - 6.3.8 Get_Sink_Cap Message 97
 - 6.3.9 DR_Swap Message 97
 - 6.3.10 PR_Swap Message 98
 - 6.3.11 VCONN_Swap Message 99
 - 6.3.12 Wait Message 99
 - 6.3.13 Soft Reset Message 100
 - 6.3.14 Not_Supported Message 100
 - 6.3.15 Get_Source_Cap_Extended Message 101
 - 6.3.16 Get_Source_Status Message 101
 - 6.3.17 FR_Swap Message 101
 - 6.4 Data Message 102
 - 6.4.1 Capabilities Message 102
 - 6.4.2 Request Message 112

6.4.3	BIST Message	116
6.4.4	Vendor Defined Message.....	117
6.4.5	Battery_Status Message.....	141
6.4.6	Source_Alert Message.....	142
6.5	Extended Message	144
6.5.1	Source_Capabilities_Extended Message	144
6.5.2	Source_Status Message	148
6.5.3	Get_Battery_Cap Message	150
6.5.4	Get_Battery_Status Message	150
6.5.5	Battery_Capabilities Message.....	151
6.5.6	Get_Manufacturer_Info Message	152
6.5.7	Manufacturer_Info Message	152
6.5.8	Security Messages	153
6.6	Timers	154
6.6.1	CRCReceiveTimer	154
6.6.2	SenderResponseTimer	154
6.6.3	Capability Timers.....	155
6.6.4	SinkRequestTimer	155
6.6.5	Power Supply Timers.....	156
6.6.6	NoResponseTimer	157
6.6.7	BIST Timers	158
6.6.8	Power Role Swap Timers.....	158
6.6.9	Hard Reset Timers.....	159
6.6.10	Structured VDM Timers	159
6.6.11	VCONN Timers.....	161
6.6.12	tCableMessage.....	161
6.6.13	DiscoverIdentityTimer	161
6.6.14	Collision Avoidance Timers.....	161
6.6.15	tFRSwapInit.....	162
6.6.16	Time Values and Timers	162
6.7	Counters.....	164
6.7.1	MessageID Counter	164
6.7.2	Retry Counter	165
6.7.3	Hard Reset Counter	165
6.7.4	Capabilities Counter	165
6.7.5	Discover Identity Counter	166
6.7.6	VDMBusyCounter	166
6.7.7	Counter Values and Counters	166
6.8	Reset.....	166
6.8.1	Soft Reset and Protocol Error	166
6.8.2	Hard Reset	167
6.8.3	Cable Reset.....	168
6.9	Collision Avoidance	168
6.10	Message Discarding.....	169
6.11	State behavior	169
6.11.1	Introduction to state diagrams used in Chapter 6	169
6.11.2	State Operation	170
6.11.3	List of Protocol Layer States.....	181
6.12	Message Applicability	182

- 6.12.1 Applicability of Control Messages 183
- 6.12.2 Applicability of Data Messages 185
- 6.12.3 Applicability of Extended Messages 185
- 6.12.4 Applicability of VDM Commands 186
- 6.12.5 Applicability of Reset Signaling 187
- 6.12.6 Applicability of Fast Role Swap signal 187
- 6.13 Value Parameters 188
- 7 Power Supply 188
 - 7.1 Source Requirements 188
 - 7.1.1 Behavioral Aspects 188
 - 7.1.2 Source Bulk Capacitance 188
 - 7.1.3 Types of Sources 189
 - 7.1.4 Positive Voltage Transitions 189
 - 7.1.5 Negative Voltage Transitions 190
 - 7.1.6 Response to Hard Resets 191
 - 7.1.7 Changing the Output Power Capability 192
 - 7.1.8 Robust Source Operation 192
 - 7.1.9 Output Voltage Tolerance and Range 193
 - 7.1.10 Charging and Discharging the Bulk Capacitance on V_{BUS} 194
 - 7.1.11 Swap Standby for Sources 194
 - 7.1.12 Source Peak Current Operation 195
 - 7.1.13 Source Capabilities Extended Parameters 195
 - 7.1.14 Fast Role Swap 197
 - 7.2 Sink Requirements 198
 - 7.2.1 Behavioral Aspects 198
 - 7.2.2 Sink Bulk Capacitance 198
 - 7.2.3 Sink Standby 199
 - 7.2.4 Suspend Power Consumption 199
 - 7.2.5 Zero Negotiated Current 199
 - 7.2.6 Transient Load Behavior 199
 - 7.2.7 Swap Standby for Sinks 200
 - 7.2.8 Sink Peak Current Operation 200
 - 7.2.9 Robust Sink Operation 200
 - 7.2.10 Fast Role Swap 201
 - 7.3 Transitions 202
 - 7.3.1 Increasing the Current 203
 - 7.3.2 Increasing the Voltage 204
 - 7.3.3 Increasing the Voltage and Current 206
 - 7.3.4 Increasing the Voltage and Decreasing the Current 208
 - 7.3.5 Decreasing the Voltage and Increasing the Current 210
 - 7.3.6 Decreasing the Current 212
 - 7.3.7 Decreasing the Voltage 214
 - 7.3.8 Decreasing the Voltage and the Current 216
 - 7.3.9 Sink Requested Power Role Swap 218
 - 7.3.10 Source Requested Power Role Swap 221
 - 7.3.11 GotoMin Current Decrease 223
 - 7.3.12 Source Initiated Hard Reset 224
 - 7.3.13 Sink Initiated Hard Reset 225
 - 7.3.14 No change in Current or Voltage 226

7.3.15	Fast Role Swap	227
7.4	Electrical Parameters	229
7.4.1	Source Electrical Parameters.....	229
7.4.2	Sink Electrical Parameters.....	231
7.4.3	Common Electrical Parameters.....	233
8	Device Policy.....	233
8.1	Overview	233
8.2	Device Policy Manager	233
8.2.1	Capabilities	234
8.2.2	System Policy.....	235
8.2.3	Control of Source/Sink.....	235
8.2.4	Cable Detection.....	235
8.2.5	Managing Power Requirements	236
8.2.6	Use of “Externally Powered” bit with Batteries and AC supplies	238
8.2.7	Interface to the Policy Engine	239
8.3	Policy Engine.....	240
8.3.1	Introduction	240
8.3.2	Atomic Message Sequence Diagrams	240
8.3.3	State Diagrams.....	341
9	States and Status Reporting	418
9.1	Overview	418
9.1.1	PDUSB Device and Hub Requirements	420
9.1.2	Mapping to USB Device States	420
9.1.3	PD Software Stack.....	423
9.1.4	PDUSB Device Enumeration.....	423
9.2	PD Class Specific Descriptors.....	424
9.2.1	USB Power Delivery Capability Descriptor	425
9.2.2	Battery Info Capability Descriptor	427
9.2.3	PD Consumer Port Capability Descriptor	427
9.2.4	PD Provider Port Capability Descriptor	428
9.3	PD Class Specific Requests and Events	429
9.3.1	Class-specific Requests	429
9.4	PDUSB Hub and PDUSB Peripheral Device Requests	430
9.4.1	GetBatteryStatus	430
9.4.2	SetPDFeature.....	432
10	Power Rules	433
10.1	Introduction.....	433
10.2	Source Power Rules	433
10.2.1	Source Power Rule Considerations.....	433
10.2.2	Normative Voltages and Currents	434
10.2.3	Optional Voltages/Currents.....	437
10.2.4	Power sharing between ports.....	437
10.3	Sink Power Rules.....	437
10.3.1	Sink Power Rule Considerations	437
10.3.2	Normative Sink Rules	437
A.	CRC calculation.....	438
A.1	C code example	438
A.2	Table showing the full calculation over one Message	439

- B PD Message Sequence Examples 439
 - B.1 External power is supplied downstream 440
 - B.2 External power is supplied upstream 443
 - B.3 Giving back power 448
- C. VDM Command Examples 456
 - C.1 Discover Identity Example 456
 - C.1.1 Discover Identity Command request 456
 - C.1.2 Discover Identity Command response – Active Cable 457
 - C.1.3 Discover Identity Command response – Hub 459
 - C.2 Discover SVIDs Example 460
 - C.2.1 Discover SVIDs Command request 460
 - C.2.2 Discover SVIDs Command response 460
 - C.3 Discover Modes Example 461
 - C.3.1 Discover Modes Command request 461
 - C.3.2 Discover Modes Command response 462
 - C.4 Enter Mode Example 463
 - C.4.1 Enter Mode Command request 463
 - C.4.2 Enter Mode Command response 464
 - C.4.3 Enter Mode Command request with additional VDO 465
 - C.5 Exit Mode Example 466
 - C.5.1 Exit Mode Command request 466
 - C.5.2 Exit Mode Command response 467
 - C.6 Attention Example 468
 - C.6.1 Attention Command request 468
 - C.6.2 Attention Command request with additional VDO 469

List of Tables

- Table 1-1 – Terms and Abbreviations 33
- Table 5-1 – 4b5b Symbol Encoding Table 57
- Table 5-2 – Ordered Sets 58
- Table 5-3 – Validation of Ordered Sets 58
- Table 5-4 – Data Size 59
- Table 5-5 – SOP ordered set 60
- Table 5-6 – SOP' ordered set 61
- Table 5-7 – SOP'' ordered set 61
- Table 5-8 – SOP'_Debug ordered set 62
- Table 5-9 – SOP''_Debug ordered set 62
- Table 5-10 – CRC-32 Mapping 64
- Table 5-11 – Hard Reset ordered set 65
- Table 5-12 – Cable Reset ordered set 66
- Table 5-13 – Rp values used for Collision Avoidance 67
- Table 5-14 – BMC Tx Mask Definition, X Values 73
- Table 5-15 – BMC Tx Mask Definition, Y Values 73
- Table 5-16 – BMC Rx Mask Definition 78

Table 5-17 – BMC Common Normative Requirements.....	80
Table 5-18 – BMC Transmitter Normative Requirements.....	81
Table 5-19 – BMC Receiver Normative Requirements.....	84
Table 6-1 – Message Header.....	89
Table 6-2 – Revision Interoperability.....	91
Table 6-3 – Extended Message Header.....	92
Table 6-4 – Control Message Types.....	95
Table 6-5 – Data Message Types.....	102
Table 6-6 – Power Data Object.....	103
Table 6-7 – Fixed Supply PDO – Source.....	106
Table 6-8 – Fixed Power Source Peak Current Capability.....	108
Table 6-9 – Variable Supply (non-Battery) PDO – Source.....	108
Table 6-10 – Battery Supply PDO – Source.....	109
Table 6-11 – Fixed Supply PDO – Sink.....	110
Table 6-12 – Variable Supply (non-Battery) PDO – Sink.....	111
Table 6-13 – Battery Supply PDO – Sink.....	111
Table 6-14 – Fixed and Variable Request Data Object.....	112
Table 6-15 – Fixed and Variable Request Data Object with GiveBack Support.....	112
Table 6-16 – Battery Request Data Object.....	113
Table 6-17 – Battery Request Data Object with GiveBack Support.....	113
Table 6-18 – BIST Data Object.....	117
Table 6-19 – Unstructured VDM Header.....	119
Table 6-20 – Structured VDM Header.....	120
Table 6-21 – Structured VDM Commands.....	120
Table 6-22 – SVID Values.....	121
Table 6-23 – Commands and Responses.....	123
Table 6-24 – ID Header VDO.....	124
Table 6-25 – Product Types (UFP).....	125
Table 6-26 – Product Types (Cable Plug).....	125
Table 6-27 – Product Types (DFP).....	126
Table 6-28 – Cert Stat VDO.....	126
Table 6-29 – Product VDO.....	126
Table 6-30 – Passive Cable VDO.....	127
Table 6-31 – Active Cable VDO.....	129
Table 6-32 – AMA VDO.....	131
Table 6-33 – Discover SVIDs Responder VDO.....	132
Table 6-34 – Battery Status Data Object (BSDO).....	141
Table 6-35 – Source Alert Data Object.....	142
Table 6-36 – Extended Message Types.....	144
Table 6-37 – Source Capabilities Extended Data Block (SCEDB).....	145
Table 6-38 – Source Status Data Block (SSDB).....	149
Table 6-39 – Get Battery Cap Data Block (GBCDB).....	150
Table 6-40 – Get Battery Status Data Block (GBSDB).....	150

Table 6-41 – Battery Capability Data Block (BCDB)	151
Table 6-42 – Get Serial Number Data Block (GSNDB)	152
Table 6-43 – Manufacturer Info Data Block (MIDB)	153
Table 6-44 – Time Values	163
Table 6-45 – Timers	164
Table 6-46 – Counter parameters	166
Table 6-47 – Counters	166
Table 6-48 – Message discarding	169
Table 6-49 – Protocol Layer States	182
Table 6-50 – Applicability of Control Messages	184
Table 6-51 – Applicability of Data Messages	185
Table 6-52 – Applicability of Extended Messages	186
Table 6-53 – Applicability of VDM Commands	187
Table 6-54 – Applicability of Reset Signaling	187
Table 6-55 – Applicability of Fast Role Swap signal	188
Table 6-56 – Value Parameters	188
Table 7-1 – Sequence Description for Increasing the Current	204
Table 7-2 – Sequence Description for Increasing the Voltage	206
Table 7-3 – Sequence Diagram for Increasing the Voltage and Current	208
Table 7-4 – Sequence Description for Increasing the Voltage and Decreasing the Current	210
Table 7-5 – Sequence Description for Decreasing the Voltage and Increasing the Current	212
Table 7-6 – Sequence Description for Decreasing the Current	214
Table 7-7 – Sequence Description for Decreasing the Voltage	216
Table 7-8 – Sequence Description for Decreasing the Voltage and the Current	218
Table 7-9 – Sequence Description for a Sink Requested Power Role Swap	220
Table 7-10 – Sequence Description for a Source Requested Power Role Swap	222
Table 7-11 – Sequence Description for a GotoMin Current Decrease	224
Table 7-12 – Sequence Description for a Source Initiated Hard Reset	225
Table 7-13 – Sequence Description for a Sink Initiated Hard Reset	226
Table 7-14 – Sequence Description for no change in Current or Voltage	227
Table 7-15 – Sequence Description for Fast Role Swap	229
Table 7-16 – Source Electrical Parameters	230
Table 7-17 – Sink Electrical Parameters	232
Table 7-18 – Common Source/Sink Electrical Parameters	233
Table 8-1 – Basic Message Flow	242
Table 8-2 – Potential issues in Basic Message Flow	243
Table 8-3 – Basic Message Flow with CRC failure	245
Table 8-4 – Interruptible and Non-interruptible AMS	246
Table 8-5 – Steps for a successful Power Negotiation	248
Table 8-6 – Steps for a GotoMin Negotiation	251
Table 8-7 – Steps for a Soft Reset	253
Table 8-8 – Steps for Source initiated Hard Reset	255

Table 8-9 – Steps for Sink initiated Hard Reset.....	258
Table 8-10 – Steps for Source initiated Hard Reset – Sink long reset.....	261
Table 8-11 – Steps for a Successful Source Initiated Power Role Swap Sequence	264
Table 8-12 – Steps for a Successful Sink Initiated Power Role Swap Sequence	268
Table 8-13 – Steps for a Successful Fast Role Swap Sequence.....	272
Table 8-14 – Steps for Data Role Swap, UFP operating as Sink initiates	276
Table 8-15 – Steps for Data Role Swap, UFP operating as Source initiates	278
Table 8-16 – Steps for Data Role Swap, DFP operating as Source initiates	280
Table 8-17 – Steps for Data Role Swap, DFP operating as Sink initiates	282
Table 8-18 – Steps for Source to Sink VCONN Source Swap.....	284
Table 8-19 – Steps for Sink to Source VCONN Source Swap.....	287
Table 8-20 – Steps for Source Alert to Sink	289
Table 8-21 – Steps for a Sink getting Source status Sequence	291
Table 8-22 – Steps for a Sink getting Source capabilities Sequence	293
Table 8-23 – Steps for a Dual-Role Source getting Dual-Role Sink’s capabilities as a Source Sequence	295
Table 8-24 – Steps for a Source getting Sink capabilities Sequence	297
Table 8-25 – Steps for a Dual-Role Sink getting Dual-Role Source capabilities as a Sink Sequence.....	299
Table 8-26 – Steps for a Sink getting Source extended capabilities Sequence	301
Table 8-27 – Steps for a Dual-Role Source getting Dual-Role Sink extended capabilities Sequence	303
Table 8-28 – Steps for a Sink getting Source Battery capabilities Sequence	305
Table 8-29 – Steps for a Source getting Sink Battery capabilities Sequence	307
Table 8-30 – Steps for a Source getting Sink’s Port Manufacturer information Sequence	309
Table 8-31 – Steps for a Source getting Sink’s Port Manufacturer information Sequence	311
Table 8-32 – Steps for a Source getting Sink’s Battery Manufacturer information Sequence	313
Table 8-33 – Steps for a Source getting Sink’s Battery Manufacturer information Sequence	315
Table 8-34 – Steps for a Source getting Sink’s Port Manufacturer information Sequence	317
Table 8-35 – Steps for a Source requesting a security exchange with a Sink Sequence.....	319
Table 8-36 – Steps for a Sink requesting a security exchange with a Source Sequence.....	321
Table 8-37 – Steps for a Vconn Source requesting a security exchange with a Cable Plug Sequence	323
Table 8-38 – Steps for DFP to UFP Discover Identity.....	325
Table 8-39 – Steps for Source Port to Cable Plug Discover Identity	327
Table 8-40 – Steps for DFP to Cable Plug Discover Identity.....	329
Table 8-41 – Steps for DFP to UFP Enter Mode.....	331
Table 8-42 – Steps for DFP to UFP Exit Mode	333
Table 8-43 – Steps for DFP to Cable Plug Enter Mode.....	335
Table 8-44 – Steps for DFP to Cable Plug Exit Mode	337
Table 8-45 – Steps for UFP to DFP Attention.....	339

Table 8-46 – Steps for BIST Eye Pattern Test..... 341

Table 8-47 – Policy Engine States 414

Table 9-1 – USB Power Delivery Type Codes 424

Table 9-2 – USB Power Delivery Capability Descriptor..... 425

Table 9-3 – Battery Info Capability Descriptor 427

Table 9-4 – PD Consumer Port Descriptor 428

Table 9-5 – PD Provider Port Descriptor 429

Table 9-6 – PD Class Requests 429

Table 9-7 – PD Class Request Codes 430

Table 9-8 – PD Class Feature Selectors 430

Table 9-9 – Battery Status Structure 431

Table 9-10 – Battery Wake Mask 432

Table 9-11 – Charging Policy Encoding 433

Table 10-1 – Considerations for Sources 434

Table 10-2 – Normative Voltages and Currents 434

Table 10-3 – Fixed Supply PDO – Source 5V..... 436

Table 10-4 – Fixed Supply PDO – Source 9V..... 436

Table 10-5 – Fixed Supply PDO – Source 15V..... 436

Table 10-6 – Fixed Supply PDO – Source 20V..... 437

Table B-1 – External power is supplied downstream..... 441

Table B-2 – External power is supplied downstream..... 444

Table B-3 – Giving back power..... 449

Table C-1 – Discover Identity Command request from Initiator Example..... 457

Table C-2 – Discover Identity Command response from Active Cable Responder Example 458

Table C-3 – Discover Identity Command response from Hub Responder Example..... 459

Table C-4 – Discover SVIDs Command request from Initiator Example 460

Table C-5 – Discover SVIDs Command response from Responder Example..... 461

Table C-6 – Discover Modes Command request from Initiator Example..... 462

Table C-7 – Discover Modes Command response from Responder Example 463

Table C-8 – Enter Mode Command request from Initiator Example..... 464

Table C-9 – Enter Mode Command response from Responder Example 465

Table C-10 – Enter Mode Command request from Initiator Example 466

Table C-11 – Exit Mode Command request from Initiator Example 467

Table C-12 – Exit Mode Command response from Responder Example 468

Table C-13 – Attention Command request from Initiator Example 469

Table C-14 – Attention Command request from Initiator with additional VDO Example 470

List of Figures

Figure 2-1 – Logical Structure of USB Power Delivery Capable Devices 41

Figure 2-2 – Example SOP' Communication between VCONN Source and Cable Plug(s) 44

Figure 2-3 – USB Power Delivery Communications Stack 49

Figure 2-4 – USB Power Delivery Communication Over USB	50
Figure 2-5 – High Level Architecture View	51
Figure 5-1 – Interpretation of ordered sets	58
Figure 5-2 – Transmit Order for Various Sizes of Data	59
Figure 5-3 – USB Power Delivery Packet Format	60
Figure 5-4 – CRC 32 generation	63
Figure 5-5 – Line format of Hard Reset	65
Figure 5-6 – Line format of Cable Reset	66
Figure 5-7 – BMC Example	67
Figure 5-8 – BMC Transmitter Block Diagram	68
Figure 5-9 – BMC Receiver Block Diagram	68
Figure 5-10 – BMC Encoded Start of Preamble	69
Figure 5-11 – Transmitting or Receiving BMC Encoded Frame Terminated by Zero with High-to-Low Last Transition	69
Figure 5-12 – Transmitting or Receiving BMC Encoded Frame Terminated by One with High-to-Low Last Transition	70
Figure 5-13 – Transmitting or Receiving BMC Encoded Frame Terminated by Zero with Low to High Last Transition	70
Figure 5-14 – Transmitting or Receiving BMC Encoded Frame Terminated by One with Low to High Last Transition	71
Figure 5-15 – Waiting for idle after a BMC Encoded Frame Terminated by Zero with High-to-Low Last Transition	71
Figure 5-16 – BMC Tx ‘ONE’ Mask	72
Figure 5-17 – BMC Tx ‘ZERO’ Mask	72
Figure 5-18 – BMC Rx ‘ONE’ Mask when Sourcing Power	75
Figure 5-19 – BMC Rx ‘ZERO’ Mask when Sourcing Power	75
Figure 5-20 – BMC Rx ‘ONE’ Mask when Power neutral	76
Figure 5-21 – BMC Rx ‘ZERO’ Mask when Power neutral	76
Figure 5-22 – BMC Rx ‘ONE’ Mask when Sinking Power	77
Figure 5-23 – BMC Rx ‘ZERO’ Mask when Sinking Power	77
Figure 5-24 – Transmitter Load Model for BMC Tx from a Source	78
Figure 5-25 Transmitter Load Model for BMC Tx from a Sink	79
Figure 5-26 – Transmitter diagram illustrating zDriver	82
Figure 5-27 – Inter-Frame Gap Timings	83
Figure 5-28 – Example Multi-Drop Configuration showing two DRPs	85
Figure 5-29 – Example Multi-Drop Configuration showing a DFP and UFP	85
Figure 5-30 – Test Data Frame	87
Figure 6-1 – USB Power Delivery Packet Format including Control Message Payload	88
Figure 6-2 – USB Power Delivery Packet Format including Data Message Payload	88
Figure 6-3 – USB Power Delivery Packet Format including an Extended Message Header and Payload	88
Figure 6-4 – Example Security_Request sequence Unchunked	93
Figure 6-5 – Example Security_Request sequence Chunked	94
Figure 6-6 – Example Capabilities Message with 2 Power Data Objects	103
Figure 6-7 – BIST Message	116

Figure 6-8 – Vendor Defined Message 118

Figure 6-9 – Discover Identity Command response 124

Figure 6-10 – Example Discover SVIDs response with 3 SVIDs 132

Figure 6-11 – Example Discover SVIDs response with 4 SVIDs 133

Figure 6-12 – Example Discover SVIDs response with 12 SVIDs followed by an empty response..... 133

Figure 6-13 – Example Discover Modes response for a given SVID with 3 Modes..... 133

Figure 6-14 – Successful Enter Mode sequence 135

Figure 6-15 – Enter Mode sequence Interrupted by Source Capabilities and then Re-run..... 135

Figure 6-16 – Unsuccessful Enter Mode sequence due to NAK..... 136

Figure 6-17 – Exit Mode sequence..... 137

Figure 6-18 – Attention Command request/response sequence..... 137

Figure 6-19 – Command request/response sequence..... 138

Figure 6-20 – Enter/Exit Mode Process..... 140

Figure 6-21 – Battery_Status Message 141

Figure 6-22 – Source_Alert Message 142

Figure 6-23 – Source_Capabilites_Extended Message..... 144

Figure 6-24 Source_Status Message 148

Figure 6-25 – Get_Battery_Cap Message 150

Figure 6-26 – Get_Battery_Status Message..... 150

Figure 6-27 – Battery_Capabilities Message 151

Figure 6-28 – Get_Manufacturer_Info Message 152

Figure 6-29 – Manufacturer_Info Message..... 152

Figure 6-30 – Security_Request Message..... 154

Figure 6-31 – Security_Response Message 154

Figure 6-32 – Outline of States 169

Figure 6-33 – References to states 170

Figure 6-34 – Common Protocol Layer Message transmission State Diagram 171

Figure 6-35 – Source Protocol Layer Message transmission State Diagram..... 174

Figure 6-36 – Sink Protocol Layer Message transmission State Diagram 176

Figure 6-37 – Protocol layer Message reception 177

Figure 6-38 – Hard/Cable Reset..... 179

Figure 7-1 – Placement of Source Bulk Capacitance..... 189

Figure 7-2 – Transition Envelope for Positive Voltage Transitions 190

Figure 7-3 – Transition Envelope for Negative Voltage Transitions 191

Figure 7-4 – Source V_{BUS} Response to Hard Reset..... 192

Figure 7-5 – Application of v_{SrcNew} and $v_{SrcValid}$ limits after $t_{SrcReady}$ 194

Figure 7-6 – Source Peak Current Overload..... 195

Figure 7-7 – Holdup Time Measurement 196

Figure 7-8 – V_{BUS} Power during Fast Role Swap..... 198

Figure 7-9 – Placement of Sink Bulk Capacitance 199

Figure 7-10 – Transition Diagram for Increasing the Current 203

Figure 7-11 – Transition Diagram for Increasing the Voltage..... 205

Figure 7-12 – Transition Diagram for Increasing the Voltage and Current	207
Figure 7-13 – Transition Diagram for Increasing the Voltage and Decreasing the Current	209
Figure 7-14 – Transition Diagram for Decreasing the Voltage and Increasing the Current	211
Figure 7-15 – Transition Diagram for Decreasing the Current.....	213
Figure 7-16 – Transition Diagram for Decreasing the Voltage	215
Figure 7-17 – Transition Diagram for Decreasing the Voltage and the Current	217
Figure 7-18 – Transition Diagram for a Sink Requested Power Role Swap.....	219
Figure 7-19 – Transition Diagram for a Source Requested Power Role Swap.....	221
Figure 7-20 – Transition Diagram for a GotoMin Current Decrease	223
Figure 7-21 – Transition Diagram for a Source Initiated Hard Reset.....	225
Figure 7-22 – Transition Diagram for a Sink Initiated Hard Reset.....	226
Figure 7-23 – Transition Diagram for no change in Current or Voltage	227
Figure 7-24 – Transition Diagram for Fast Role Swap	228
Figure 8-1 – Example of daisy chained displays.....	239
Figure 8-2 – Basic Message Exchange (Successful)	241
Figure 8-3 – Basic Message flow indicating possible errors.....	242
Figure 8-4 – Basic Message Flow with Bad CRC followed by a Retry.....	244
Figure 8-5 – Successful Power Negotiation.....	247
Figure 8-6 – Successful GotoMin operation.....	250
Figure 8-7 – Soft Reset.....	252
Figure 8-8 – Source initiated Hard Reset	254
Figure 8-9 – Sink Initiated Hard Reset	257
Figure 8-10 – Source initiated reset – Sink long reset	260
Figure 8-11 – Successful Power Role Swap Sequence Initiated by the Source	263
Figure 8-12 – Successful Power Role Swap Sequence Initiated by the Sink.....	267
Figure 8-13 – Successful Fast Role Swap Sequence	271
Figure 8-14 – Data Role Swap, UFP operating as Sink initiates	275
Figure 8-15 – Data Role Swap, UFP operating as Source initiates	277
Figure 8-16 – Data Role Swap, DFP operating as Source initiates	279
Figure 8-17 – Data Role Swap, DFP operating as Sink initiates	281
Figure 8-18 – Source to Sink VCONN Source Swap.....	283
Figure 8-19 – Sink to Source VCONN Source Swap.....	286
Figure 8-20 – Source Alert to Sink	289
Figure 8-21 – Sink Gets Source Status	290
Figure 8-22 – Sink Gets Source’s Capabilities	292
Figure 8-23 – Dual-Role Source Gets Dual-Role Sink’s Capabilities as a Source	294
Figure 8-24 – Source Gets Sink’s Capabilities	296
Figure 8-25 – Dual-Role Sink Gets Dual-Role Source’s Capabilities as a Sink	298
Figure 8-26 – Sink Gets Source’s Extended Capabilities.....	300
Figure 8-27 – Dual-Role Source Gets Dual-Role Sink’s Extended Capabilities	302
Figure 8-28 – Sink Gets Source’s Battery Capabilities	304
Figure 8-29 – Source Gets Sink’s Battery Capabilities	306

Figure 8-30 – Source Gets Sink’s Port Manufacturer Information	308
Figure 8-31 – Sink Gets Source’s Port Manufacturer Information	310
Figure 8-32 – Source Gets Sink’s Battery Manufacturer Information.....	312
Figure 8-33 – Sink Gets Source’s Battery Manufacturer Information.....	314
Figure 8-34 – VCONN Source Gets Cable Plug’s Manufacturer Information	316
Figure 8-35 – Source requests security exchange with Sink.....	318
Figure 8-36 – Sink requests security exchange with Source.....	320
Figure 8-37 – Vconn Source requests security exchange with Cable Plug	322
Figure 8-38 – DFP to UFP Discover Identity.....	324
Figure 8-39 – Source Port to Cable Plug Discover Identity.....	326
Figure 8-40 – DFP to Cable Plug Discover Identity	328
Figure 8-41 – DFP to UFP Enter Mode.....	330
Figure 8-42 – DFP to UFP Exit Mode	332
Figure 8-43 – DFP to Cable Plug Enter Mode	334
Figure 8-44 – DFP to Cable Plug Exit Mode.....	336
Figure 8-45 – UFP to DFP Attention.....	338
Figure 8-46 – BIST Carrier Mode Test	340
Figure 8-47 – Outline of States	342
Figure 8-48 – References to states	342
Figure 8-49 – Example of state reference with conditions	342
Figure 8-50 – Example of state reference with the same entry and exit.....	343
Figure 8-51 – Source Port Policy Engine state diagram	345
Figure 8-52 – Sink Port state diagram.....	351
Figure 8-53 – Source Port Soft Reset and Protocol Error State Diagram	355
Figure 8-54 – Sink Port Soft Reset and Protocol Error Diagram	356
Figure 8-55 – Source Port Not Supported Message State Diagram	358
Figure 8-56 – Sink Port Not Supported Message State Diagram	358
Figure 8-57 – Source Port Ping State Diagram.....	359
Figure 8-58 – Source Port Source Alert State Diagram	360
Figure 8-59 – Sink Port Source Alert State Diagram.....	360
Figure 8-60 – Sink Port Get Source Capabilities Extended state diagram.....	361
Figure 8-61 – Source Give Source Capabilities Extended state diagram	361
Figure 8-62 – Sink Port Get Source Status state diagram	362
Figure 8-63 – Source Give Source Status state diagram	362
Figure 8-64 – Get Battery Capabilities state diagram	363
Figure 8-65 – Give Battery Capabilities state diagram.....	363
Figure 8-66 – Get Battery Status state diagram	364
Figure 8-67 – Give Battery Status state diagram	365
Figure 8-68 – Get Manufacturer Information state diagram	365
Figure 8-69 – Give Manufacturer Information state diagram	366
Figure 8-70 – Send security request state diagram	366
Figure 8-71 – Send security response state diagram.....	367
Figure 8-72 – Security response received state diagram	367

Figure 8-73 – DFP to UFP Data Role Swap State Diagram	368
Figure 8-74 – UFP to DFP Data Role Swap State Diagram	371
Figure 8-75 – Dual-Role Port in Source to Sink Power Role Swap State Diagram	373
Figure 8-76 – Dual-role Port in Sink to Source Power Role Swap State Diagram	376
Figure 8-77 – Dual-Role Port in Source to Sink Fast Role Swap State Diagram	379
Figure 8-78 – Dual-role Port in Sink to Source Fast Role Swap State Diagram	382
Figure 8-79 – Dual-Role (Source) Get Source Capabilities diagram	384
Figure 8-80 – Dual-Role (Source) Give Sink Capabilities diagram	384
Figure 8-81 – Dual-Role (Sink) Get Sink Capabilities State Diagram	385
Figure 8-82 – Dual-Role (Sink) Give Source Capabilities State Diagram	385
Figure 8-83 – Dual-Role (Source) Get Source Capabilities Extended state diagram	386
Figure 8-84 – Dual-Role (Source) Give Sink Capabilities diagram	387
Figure 8-85 – VCONN Swap State Diagram	388
Figure 8-86 – Initiator to Port VDM Discover Identity State Diagram	391
Figure 8-87 – Initiator VDM Discover SVIDs State Diagram	392
Figure 8-88 – Initiator VDM Discover Modes State Diagram	393
Figure 8-89 – Initiator VDM Attention State Diagram	394
Figure 8-90 – Responder Structured VDM Discover Identity State Diagram	395
Figure 8-91 – Responder Structured VDM Discover SVIDs State Diagram	396
Figure 8-92 – Responder Structured VDM Discover Modes State Diagram	397
Figure 8-93 – Receiving a Structured VDM Attention State Diagram	398
Figure 8-94 – DFP VDM Mode Entry State Diagram	399
Figure 8-95 – DFP VDM Mode Exit State Diagram	400
Figure 8-96 – UFP Structured VDM Enter Mode State Diagram	401
Figure 8-97 – UFP Structured VDM Exit Mode State Diagram	402
Figure 8-98 – Cable Ready VDM State Diagram	403
Figure 8-99 – Cable Plug Soft Reset State Diagram	404
Figure 8-100 – Cable Plug Hard Reset State Diagram	405
Figure 8-101 – DFP Soft Reset or Cable Reset of a Cable Plug State Diagram	405
Figure 8-102 – UFP Source Soft Reset of a Cable Plug State Diagram	407
Figure 8-103 – Source Startup Structured VDM Discover Identity State Diagram	408
Figure 8-104 – Cable Plug Structured VDM Enter Mode State Diagram	410
Figure 8-105 – Cable Plug Structured VDM Exit Mode State Diagram	411
Figure 8-106 – BIST Carrier Mode State Diagram	412
Figure 9-1 – Example PD Topology	419
Figure 9-2 – Mapping of PD Topology to USB	420
Figure 9-3 – USB Attached to USB Powered State Transition	421
Figure 9-4 – Any USB State to USB Attached State Transition (When operating as a Consumer)	422
Figure 9-5 – Any USB State to USB Attached State Transition (When operating as a Provider)	422
Figure 9-6 – Any USB State to USB Attached State Transition (After a USB Type-C Data Role Swap)	423
Figure 9-7 – Software stack on a PD aware OS	423

Figure 9-8 – Enumeration of a PDUSB Device 424

Figure 10-1 – Source Power Rule Illustration 435

Figure 10-2 – Source Power Rule Example 435

Figure B-1 – External Power supplied downstream..... 440

Figure B-2 – External Power supplied upstream..... 443

Figure B-3 – Giving Back Power..... 448

1 Introduction

USB has evolved from a data interface capable of supplying limited power to a primary provider of power with a data interface. Today many devices charge or get their power from USB ports contained in laptops, cars, aircraft or even wall sockets. USB has become a ubiquitous power socket for many small devices such as cell phones, MP3 players and other hand-held devices. Users need USB to fulfill their requirements not only in terms of data but also to provide power to, or charge, their devices simply, often without the need to load a driver, in order to carry out “traditional” USB functions.

There are however, still many devices which either require an additional power connection to the wall, or exceed the USB rated current in order to operate. Increasingly, international regulations require better energy management due to ecological and practical concerns relating to the availability of power. Regulations limit the amount of power available from the wall which has led to a pressing need to optimize power usage. The USB Power Delivery Specification has the potential to minimize waste as it becomes a standard for charging devices that are not satisfied by [\[USBBC 1.2\]](#).

Wider usage of wireless solutions is an attempt to remove data cabling but the need for “tethered” charging remains. In addition, industrial design requirements drive wired connectivity to do much more over the same connector.

USB Power Delivery is designed to enable the maximum functionality of USB by providing more flexible power delivery along with data over a single cable. Its aim is to operate with and build on the existing USB ecosystem; increasing power levels from existing USB standards, for example Battery Charging, enabling new higher power use cases such as USB powered Hard Disk Drives (HDDs) and printers.

With USB Power Delivery the power direction is no longer fixed. This enables the product with the power (Host or Peripheral) to provide the power. For example, a display with a supply from the wall can power, or charge, a laptop. Alternatively, USB power bricks or chargers are able to supply power to laptops and other battery powered devices through their, traditionally power providing, USB ports.

USB Power Delivery enables hubs to become the means to optimize power management across multiple peripherals by allowing each device to take only the power it requires, and to get more power when required for a given application. For example battery powered devices can get increased charging current and then give it back temporarily when the user’s HDD requires spinning up. **Optionally** the hubs can communicate with the PC to enable even more intelligent and flexible management of power either automatically or with some level of user intervention.

USB Power Delivery allows Low Power cases such as headsets to negotiate for only the power they require. This provides a simple solution that enables USB devices to operate at their optimal power levels.

The Power Delivery Specification, in addition to providing mechanisms to negotiate power also can be used as a side-band channel for standard and vendor defined messaging. Power Delivery enables alternative modes of operation by providing the mechanisms to discover, enter and exit Alternate Modes. The specification also enables discovery of cable capabilities such as supported speeds and current levels.

1.1 Overview

This specification defines how USB Devices may negotiate for more current and/or higher or lower voltages over the USB cable (using the USB Type-C CC wire as the communications

channel) than are defined in the [\[USB 2.0\]](#), [\[USB 3.1\]](#), [\[USB Type-C 1.2\]](#) or [\[USBBC 1.2\]](#) specifications. It allows Devices with greater power requirements than can be met with today's specification to get the power they require to operate from V_{BUS} and negotiate with external power sources (e.g. wall warts). In addition, it allows a Source and Sink to swap power roles such that a Device could supply power to the Host. For example, a display could supply power to a notebook to charge its battery.

The USB Power Delivery Specification is guided by the following principles:

- 1) Works seamlessly with legacy USB Devices
- 2) Compatible with existing spec-compliant USB cables
- 3) Minimizes potential damage from non-compliant cables (e.g. 'Y' cables etc.)
- 4) Optimized for low-cost implementations

This specification defines mechanisms to discover, enter and exit Modes defined either by a standard or by a particular vendor. These Modes can be supported either by the Port Partner or by a cable connecting the two Port Partners.

The specification defines mechanisms to discover the capabilities of cables which can communicate using Power Delivery.

This specification adds a mechanism to swap the data roles such that the upstream facing Port becomes the downstream facing Port and vice versa. It also enables a swap of the end supplying V_{CONN} to a powered cable.

1.2 Purpose

The USB Power Delivery specification defines a power delivery system covering all elements of a USB system including: Hosts, Devices, Hubs, Chargers and cable assemblies. This specification describes the architecture, protocols, power supply behavior, connectors and cabling necessary for managing power delivery over USB at up to 100W. This specification is intended to be fully compatible and extend the existing USB infrastructure. It is intended that this specification will allow system OEMs, power supply and peripheral developers adequate flexibility for product versatility and market differentiation without losing backwards compatibility.

USB Power Delivery is designed to operate independently of the existing USB bus defined mechanisms used to negotiate power which are:

- [\[USB 2.0\]](#), [\[USB 3.1\]](#) in band requests for high power interfaces.
- [\[USBBC 1.2\]](#) mechanisms for supplying higher power (not mandated by this specification).
- [\[USB Type-C 1.2\]](#) mechanisms for supplying higher power

Initial operating conditions remain the USB Default Operation as defined in [\[USB 2.0\]](#), [\[USB 3.1\]](#), [\[USB Type-C 1.2\]](#) or [\[USBBC 1.2\]](#).

- The DFP sources *vSafe5V* over V_{BUS} .
- The UFP consumes power from V_{BUS} .

1.3 Scope

This specification is intended as an extension to the existing [\[USB 2.0\]](#), [\[USB 3.1\]](#), [\[USB Type-C 1.2\]](#) and [\[USBBC 1.2\]](#) specifications. It addresses only the elements required to implement USB Power Delivery. It is targeted at power supply vendors, manufacturers of [\[USB 2.0\]](#), [\[USB 3.1\]](#), [\[USB Type-C 1.2\]](#) and [\[USBBC 1.2\]](#) Platforms, Devices and cable assemblies.