



BSI Standards Publication

Test methods for quantitative determination of corrosive sulfur compounds in unused and used insulating liquids

Part 3: Test method for quantitative determination of elemental sulfur

National foreword

This Published Document is the UK implementation of IEC/TR 62697-3:2018.

The UK participation in its preparation was entrusted to Technical Committee GEL/10, Fluids for electrotechnical applications.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2018
Published by BSI Standards Limited 2018

ISBN 978 0 580 97762 6

ICS 29.040.10

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 March 2018.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------



TECHNICAL REPORT



**Test methods for quantitative determination of corrosive sulfur compounds in
unused and used insulating liquids –
Part 3: Test method for quantitative determination of elemental sulfur**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 29.040.10

ISBN 978-2-8322-5361-8

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	8
2 Normative references	8
3 Terms and definitions	8
4 Sampling	9
5 Procedure.....	9
5.1 Principle	9
5.1.1 Determination with gas chromatography	9
5.1.2 Determination with differential pulse voltammetry	9
5.2 Significance and use.....	9
5.3 Interferences.....	10
5.3.1 Co-eluting compounds	10
5.3.2 Electron capture detector (ECD)	10
5.3.3 Flame photometric detector (FPD)	10
5.3.4 Mass spectrometer (MS).....	10
5.3.5 Interference from the matrix.....	10
5.4 Apparatus	10
5.4.1 Balance	10
5.4.2 Gas chromatography system	11
5.4.3 Differential pulsed voltammetry.....	11
5.5 Reagents and materials	11
5.5.1 Purity of reagents	11
5.5.2 Gases.....	11
5.5.3 Solvents	12
5.6 Standard materials.....	12
5.6.1 Elemental sulfur.....	12
5.6.2 Diphenyl disulfide (DPDS)	12
5.6.3 Blank oil	12
5.7 Standard solutions	12
5.7.1 Stock solutions	12
5.7.2 Internal standard (IS) solution.....	13
6 Instrument set-up	13
6.1 Gas chromatograph	13
6.1.1 General	13
6.1.2 Carrier gas	13
6.1.3 Injector	13
6.1.4 Separation parameters	13
6.1.5 ECD detection	14
6.1.6 FPD detection.....	14
6.1.7 MS detection	14
6.2 Calibration	14
6.2.1 General	14
6.2.2 Calibration procedure	14
6.2.3 Response factor determination (ECD and FPD)	15
6.2.4 Response factor determination (MS).....	15

6.3	Analysis	15
6.3.1	Sample pre-treatment	15
6.3.2	Sample injection	16
6.3.3	Chromatographic run	16
6.3.4	Peak integration	16
6.4	Calculations	16
6.4.1	ECD and FPD	16
6.4.2	Mass spectrometer (MS).....	16
6.4.3	Differential pulse voltammetry measurements	17
6.5	Results	17
7	Precision data	18
7.1	Detection limit.....	18
7.2	Repeatability.....	18
7.3	Reproducibility	18
8	Report	18
Annex A (informative) Figures with typical chromatograms and results		19
Annex B (informative) RRT results Statistical evaluation of elemental sulfur data GC-ECD/FPD.....		21
Bibliography.....		23
Figure 1 – Typical peak form and concentration calculation		17
Figure A.1 – GC-ECD chromatogram of 5 mg kg ⁻¹ elemental sulfur and (IS) in white mineral oil.....		19
Figure A.2 – GC-ECD chromatogram of 100 mg kg ⁻¹ elemental sulfur and (IS) in white mineral oil.....		20
Table 1 – Column oven temperature programming parameters		14
Table 2 – Mass spectrometer parameters		14
Table 3 – Repeatability limit.....		18
Table 4 – Reproducibility limit.....		18
Table B.1 – Reproducibility with same chemical analysis approach.....		21
Table B.2 – Reproducibility with different chemical analysis approach		21
Table B.3 – Repeatability.....		22

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**TEST METHODS FOR QUANTITATIVE DETERMINATION
OF CORROSIVE SULFUR COMPOUNDS IN UNUSED
AND USED INSULATING LIQUIDS –**

**Part 3: Test method for quantitative determination
of elemental sulfur**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a Technical Report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC TR 62697-3, which is a Technical Report, has been prepared by IEC technical committee 10: Fluids for electrotechnical applications.

The text of this Technical Report is based on the following documents:

Draft TR	Report on voting
10/1014/DTR	10/1028/RVDTR

Full information on the voting for the approval of this Technical Report can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62697 series, published under the general title *Test methods for quantitative determination of corrosive sulfur compounds in unused and used insulating liquids*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

During the IEC technical committee 10 plenary meeting in 2007, it was decided to set up a working group with the aim of developing a standard on “quantitative determination of corrosive sulfur compounds in insulating fluids”.

TC 10 decided to divide the overall task into three parts:

- Part 1: Test method for quantitative determination of dibenzyl disulfide (DBDS);
- Part 2: Test method for quantitative determination of total corrosive sulfur (TCS);
- Part 3: Test method for quantitative determination of elemental sulfur.

Part 1 was published in 2012, however the work for the preparation of Part 2 and Part 3 took longer than anticipated. During the TC 10 plenary meeting in 2015, in order to finalize the important work achieved, a proposal was made to complete the work and publish Part 2 and Part 3 as Technical Reports.

Sulfur can be present in insulating liquids in various forms, including elemental sulfur, inorganic sulfur compounds and organic sulfur compounds. The number of diverse sulphur species comprised of different isomers and homologous can run into hundreds. The total sulfur (TS) concentration in insulating liquids depends on the origin of the liquid, refining processes and the degree of refining and formulation including addition of additives to the base oils. Base oils include mineral based paraffinic and naphthenic oils, synthetic iso-paraffins obtained through gas to liquid conversion process (GTL-Fischer-Tropsch), esters, poly alpha olefins, poly alkylene glycols, etc. Additives can be comprised of electrostatic discharge depressants, metal deactivators, metal passivators, phenolic and sulfur containing antioxidants such as the polysulfides, disulfides, dibenzyl disulfide (DBDS).

Certain sulfur compounds present in the insulating liquids exhibit antioxidant and metal deactivating properties without being corrosive, whereas other sulfur compounds have been known to react with metal surfaces. Specifically, sulfur compounds such as mercaptans are very corrosive to metallic components of electrical devices. Presence of these corrosive sulfur species has been linked to failures of electrical equipment used in generation, transmission and distribution of electrical energy for several decades. Therefore, IEC 60296 states that corrosive sulfur compounds shall not be present in unused and used insulating liquids.

The serious detrimental impact of corrosive sulfur has also been linked to the presence of a specific highly corrosive sulfur compound, DBDS. This compound has been found in certain mineral insulating oils [1], [15], [16], [17]¹; presence of this compound has been shown to result in copper sulfide formation on the surfaces of copper conductors under normal operating conditions of transformers [2]. It has been reported that elemental sulfur and other corrosive sulfur compounds such as mercaptans may be introduced during reclamation of mineral oil with adsorbents reactivated through a combustion process. A proposal for inclusion of a test method for quantification elemental sulfur in IEC 62697 was made by CIGRE WG A2.40. The proposal was approved by IEC TC 10 in 2013. Several methods for quantification of elemental sulfur in petroleum products and other matrices have been reported, however, methods do not directly deal with quantification of elemental sulfur in insulating oils.

However, current standard test methods for the detection of corrosive sulfur ([11] and [13]) and potentially corrosive sulfur in used and unused insulating oil [8] are empirical and qualitative. These methods rely on visual and subjective perception of colour profiles. The methods do not yield quantitative results in regard to the concentration of DBDS or other corrosive sulfur compounds present in insulating liquids.

¹ Numbers in square brackets refer to the Bibliography.

Furthermore, methods for corrosive sulfur and potentially corrosive sulfur in insulating liquids ([8] and [11]) are applicable only for mineral insulating oils that do not contain a metal passivator additive, as these methods can otherwise yield negative results even when corrosive sulfur compounds are present in the insulating liquids – thus providing a false negative test result. On the other hand, the test method when used with aged insulating oils (e.g. those with relative high acidity), may give ambiguous results and lead to a false positive test result. Further analysis of insulating liquids is stipulated, for example IEC 62535 specifies that if there are any doubts in the interpretation of the results of the inspection of paper, the composition of precipitate should be analysed by other methods (e.g. by SEM-EDX).

For this reason, a working group within IEC TC 10 was set up to prepare test methods for the unambiguous quantitative determination of corrosive sulfur compounds in unused and used insulating liquids.

WARNING – Health and safety

This part of IEC 62697 does not purport to address all the safety problems associated with its use. It is the responsibility of the user of this document to establish appropriate health and safety practices and determine the applicability of regulatory limitations prior to use.

The insulating liquids which are the subject of this document should be handled with due regard to personal hygiene. Direct contact with eyes may cause slight irritation. In the case of eye contact, irrigation with copious quantities of clean running water should be carried out and medical advice sought.

Some of the tests specified in this document involve the use of processes that could lead to a hazardous situation. Attention is drawn to the relevant standard for guidance.

WARNING – Environment

This document involves mineral insulating oils, natural ester insulating liquids, chemicals and used sample containers. The disposal of these items should be carried out in accordance with current national legislation with regard to the impact on the environment. Every precaution should be taken to prevent the release of chemicals used during the test into the environment.

TEST METHODS FOR QUANTITATIVE DETERMINATION OF CORROSIVE SULFUR COMPOUNDS IN UNUSED AND USED INSULATING LIQUIDS –

Part 3: Test method for quantitative determination of elemental sulfur

1 Scope

This part of IEC 62697 specifies a test method for the quantitative determination of elemental sulfur in used and unused insulating liquids over a 2 mg kg^{-1} to 400 mg kg^{-1} concentration range.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62697-1, *Test methods for quantitative determination of corrosive sulfur compounds in unused and used insulating liquids – Part 1: Test method for quantitative determination of dibenzyldisulfide (DBDS)*

IEC TR 62697-2, *Test methods for quantitative determination of corrosive sulfur compounds in unused and used insulating liquids – Part 2: Test method for quantitative determination of total corrosive sulfur (TCS)*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 62697-1 and IEC TR 62697-2 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

elemental sulfur

unbound form of the element with atomic number 16

Note 1 to entry: Under normal conditions, sulfur atoms occur in different forms (allotropes) of which the orthorhombic, cyclic octatomic form with chemical formula S_8 is the most abundant. This form is a bright yellow crystalline solid at room temperature.

3.2

allotropy

property of some chemical elements to exist in two or more different forms, in the same physical state