

JIS

JAPANESE
INDUSTRIAL
STANDARD

Translated and Published by
Japanese Standards Association

JIS G 3477-3 : 2018

(JISF)

**Polyethylene coated steel pipes—
Part 3: External polyethylene
powder coated steel pipes**

ICS 77.140.10;77.140.75

Reference number : **JIS G 3477-3 : 2018 (E)**

Date of Establishment: 2012-11-20

Date of Revision: 2018-03-20

Date of Public Notice in Official Gazette: 2018-03-20

Investigated by: Japanese Industrial Standards Committee
Standards Board for ISO area
Technical Committee on Metal and Inorganic
Materials

JIS G 3477-3:2018, First English edition published in 2018-09

Translated and published by: Japanese Standards Association
Mita MT Building, 3-13-12, Mita, Minato-ku, Tokyo, 108-0073 JAPAN

In the event of any doubts arising as to the contents,
the original JIS is to be the final authority.

© JSA 2018

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

AT

Contents

	Page
1	Scope 1
2	Normative references 1
3	Terms and definitions 2
4	Symbol of grade 2
5	Materials 3
5.1	Original pipes 3
5.2	Coating materials 4
6	Manufacturing method 4
6.1	Pretreatment 4
6.2	Coating method 4
6.3	Inner coating 4
7	Coated steel pipes 4
7.1	Coating performance 4
7.2	Coating thickness 5
7.3	Position and shape of coating at pipe end 5
7.4	Appearance 6
8	Test methods of coated steel pipes 6
8.1	Type of test 6
8.2	Coating thickness 6
8.3	Pinholes 7
8.4	Adhesive property 7
8.5	Peel strength test 7
8.6	Impact test 7
8.7	Indentation depth test 7
8.8	Test of nominal tensile strain at break 7
8.9	Bend test 7
8.10	Cathodic disbondment test 8
8.11	Hot water immersion test 8
9	Inspection 8
10	Repair 8
10.1	General 8
10.2	Repair range 8
10.3	Repair method 8
11	Marking 9

12	Report	9
Annex A (normative)	Polyethylene coating materials	10
Annex B (informative)	Control items of manufacturing process	13
Annex C (normative)	Peel strength test method	14
Annex D (normative)	Impact test method	15
Annex E (normative)	Indentation depth test method	16
Annex F (normative)	Bend test method	17
Annex G (normative)	Cathodic disbondment test method	19
Annex H (normative)	Hot water immersion test method	21

Foreword

This Japanese Industrial Standard has been revised by the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee as the result of proposal for revision of Japanese Industrial Standard submitted by The Japan Iron and Steel Federation (JISF) with the draft being attached, based on the provision of Article 12 Clause 1 of the Industrial Standardization Law applicable to the case of revision by the provision of Article 14.

Consequently **JIS G 3477-3**:2016 is replaced with this Standard.

This **JIS** document is protected by the Copyright Law.

Attention is drawn to the possibility that some parts of this Standard may conflict with patent rights, applications for a patent after opening to the public or utility model rights. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying any of such patent rights, applications for a patent after opening to the public or utility model rights.

JIS K 3477 series consists of the following 3 parts under the general title “*Polyethylene coated steel pipes*”:

JIS G 3477-1 *Part 1: External 3 layer extruded polyethylene coated steel pipes*

JIS G 3477-2 *Part 2: External extruded polyethylene coated steel pipes*

JIS G 3477-3 *Part 3: External polyethylene powder coated steel pipes*

Polyethylene coated steel pipes— Part 3: External polyethylene powder coated steel pipes

1 Scope

This Japanese Industrial Standard specifies the external polyethylene powder coated steel pipes (hereafter referred to as coated steel pipes) mainly used for underground¹⁾ services of transporting gas, oil, water, etc. This Standard is applicable to straight pipes and deformed pipes of outside diameter 21.7 mm (nominal diameter 15A or 1/2B) to 1 625.6 mm (nominal diameter 1 600A or 64B). The coated steel pipes are usually used at temperatures in the range of -40 °C to +60 °C.

Note ¹⁾ The underground referred to above includes the bottom of river, the bottom of sea, etc.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this Standard. The most recent editions of the standards (including amendments) indicated below shall be applied.

JIS B 2311 *Steel butt-welding pipe fittings for ordinary use*

JIS B 2312 *Steel butt-welding pipe fittings*

JIS B 2313 *Steel plate butt-welding pipe fittings*

JIS G 0404 *Steel and steel products—General technical delivery requirements*

JIS G 0415 *Steel and steel products—Inspection documents*

JIS G 3444 *Carbon steel tubes for general structure*

JIS G 3445 *Carbon steel tubes for machine structure*

JIS G 3452 *Carbon steel pipes for ordinary piping*

JIS G 3454 *Carbon steel pipes for pressure service*

JIS G 3455 *Carbon steel pipes for high pressure service*

JIS G 3457 *Arc welded carbon steel pipes*

JIS G 3460 *Steel pipes for low temperature service*

JIS K 6900 *Plastics—Vocabulary*

JIS K 6922-2 *Plastics—Polyethylene (PE) moulding and extrusion materials—
Part 2: Preparation of test specimens and determination of properties*

JIS K 7112 *Plastics—Methods of determining the density and relative density of
non-cellular plastics*

JIS K 7161-1 *Plastics—Determination of tensile properties—Part 1: General prin-
ciples*