

# FINAL VERSION

# VERSION FINALE



---

**Marking codes for resistors and capacitors**

**Codes de marquage des résistances et des condensateurs**

## CONTENTS

FOREWORD .....	4
1 Scope .....	6
2 Normative references .....	6
3 Colour code for fixed resistors .....	6
3.1 General rules .....	6
3.2 Prescription of code colours .....	6
3.3 Methods for marking resistance value and tolerance .....	7
3.3.1 Marking of resistance values with two significant numerals .....	7
3.3.2 Marking of resistance values with two significant numerals and tolerance .....	8
3.3.3 Marking of resistance values with three significant numerals and tolerance .....	8
3.4 Methods for TCR marking .....	9
4 Letter and numeral code for resistance and capacitance values .....	10
4.1 General rules .....	10
4.2 Resistors .....	11
4.2.1 The RKM code system .....	11
4.2.2 Three-character code system for resistors .....	13
4.2.3 The four-character code system for resistors .....	14
4.3 Capacitors .....	15
4.3.1 The multiplier code system for capacitors .....	15
4.3.2 Three-character code systems for capacitors .....	17
5 Letter code for tolerance on capacitance or resistance values .....	18
5.1 General rules .....	18
5.2 Coding of symmetrical relative tolerances .....	18
5.3 Coding of asymmetrical relative tolerances .....	19
5.4 Coding of symmetrical absolute tolerances .....	19
5.5 Other coding of tolerances .....	20
6 Coding of properties specific to capacitors .....	20
6.1 General rules .....	20
6.2 Coding of the dielectric material of plastic film capacitors .....	20
7 Coding of properties specific to resistors .....	20
7.1 General rules .....	20
7.2 Coding of the temperature coefficient of resistance .....	21
8 Date code system for capacitors and resistors .....	21
8.1 General rules .....	21
8.2 Two-character codes for year and month .....	22
8.2.1 Choice of a repetition cycle .....	22
8.2.2 Two-character codes for year and month in a twenty-year cycle .....	22
8.2.3 Two-character codes for year and month in a ten-year cycle .....	23
8.3 Four-character codes for year and week .....	23
8.3.1 Choice of a repetition cycle .....	23
8.3.2 Fully numerical four-numeral code .....	23
8.3.3 Alphanumerical twenty-year cycle code .....	24
8.3.4 Alphanumerical ten-year cycle code .....	24
8.4 Single-character code for year and month .....	24

Annex A (informative) Special three-character code system for resistors .....	26
Annex B (informative) Special two-character code system for capacitors .....	28
Annex X (informative) Cross-reference for references to the previous edition of this standard .....	31
Bibliography.....	33
Figure 1 – Colour marking of a resistor 6,8 kΩ, tolerance ±20 % .....	8
Figure 2 – Colour marking of a resistor 750 kΩ, tolerance ±5 % .....	8
Figure 3 – Colour marking of a resistor 249 kΩ, tolerance ±1 % .....	9
Figure 4 – Colour marking of a resistor with a 6 <sup>th</sup> band for TCR marking .....	9
Figure 5 – Colour marking of a resistor with an interrupted 6 <sup>th</sup> band for TCR marking .....	10
Figure 6 – Colour marking of a resistor using an alternative method of inter-band colour dots for TCR coding .....	10
Table 1 – Code colour prescriptions .....	7
Table 2 – Coding of resistance values with up to 3 significant numerals.....	12
Table 3 – Fixed length coding of resistance values with up to 3 significant numerals .....	13
Table 4 – Coding of resistance values with 4 significant numerals .....	13
Table 5 – Coding of resistance values in the three-character code system.....	14
Table 6 – Coding of resistance values in the four-character code system.....	15
Table 7 – Coding of capacitance values with up to 2 significant numerals .....	16
Table 8 – Fixed length coding of capacitance values with up to 2 significant numerals.....	16
Table 9 – Coding of capacitance values with 3 significant numerals.....	17
Table 10 – Coding of capacitance values in the picofarad based three-character code system.....	17
Table 11 – Coding of capacitance values in the microfarad based three-character code system.....	18
Table 12 – Letter code for symmetrical relative tolerances.....	19
Table 13 – Letter code for asymmetrical relative tolerances.....	19
Table 14 – Letter code for symmetrical absolute tolerances of capacitors .....	20
Table 15 – Letter code for the dielectric material of plastic film capacitors .....	20
Table 16 – Letter code for the temperature coefficient of resistance.....	21
Table 17 – Character code letters for the month .....	22
Table 18 – Code letters for the year in a twenty-year cycle .....	22
Table 19 – Code letters for the year in a ten-year cycle .....	23
Table 20 – Single-character code for year and month at a 4-year cycle.....	25
Table A.1 – Coding of the significant numerals of the E96 series .....	26
Table A.2 – Coding of the multiplier .....	27
Table B.1 – Coding of the significant numbers of the E24 series .....	28
Table B.2 – Coding of the multiplier .....	29
Table X.1 – Cross-reference to Clauses.....	31
Table X.2 – Cross-reference to Tables.....	32

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

## MARKING CODES FOR RESISTORS AND CAPACITORS

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

**DISCLAIMER**

**This Consolidated version is not an official IEC Standard and has been prepared for user convenience. Only the current versions of the standard and its amendment(s) are to be considered the official documents.**

**This Consolidated version of IEC 60062 bears the edition number 6.1. It consists of the sixth edition (2016-07) [documents 40/2465/FDIS and 40/2473/RVD], its corrigendum (2016-12) and its amendment 1 (2019-08) [documents 40/2622/CDV and 40/2661/RVC]. The technical content is identical to the base edition and its amendment.**

**This Final version does not show where the technical content is modified by amendment 1. A separate Redline version with all changes highlighted is available in this publication.**

International Standard IEC 60062 has been prepared by IEC technical committee 40: Capacitors and resistors for electronic equipment.

This sixth edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- introduction of the new code colour pink for the coding of the multiplier  $10^{-3}$ ;
- introduction of new subclauses, 3.2 Prescription of code colours, 3.3 Methods for marking resistance value and tolerance, 3.4 Methods for TCR marking, for improved clarity, the subjects of colour assignment, coding of R value and tolerance, and coding of TCR is dealt with in separate clauses;
- inclusion of illustrations for TCR marking by interrupted colour band;
- inclusion of a new subclause on a fixed length code marking, fixed length code marking of resistance values with up to 3 significant digits, hence a fixed code length of 4 digits, and fixed length code marking of capacitance values with up to 2 significant digits, hence a fixed code length of 3 digits;
- introduction of two new clauses, Clause 6, Coding of properties specific to capacitors and Clause 7, Coding of properties specific to resistors;
- introduction of Annex A, Special three character coding of resistance value with three significant numerals.
- introduction of Annex B, Special two-character code system for capacitors.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of the base publication and its amendment will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

**IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

# MARKING CODES FOR RESISTORS AND CAPACITORS

## 1 Scope

This International Standard specifies designation and marking codes for capacitors and resistors.

It provides coding methods for the resistance or capacitance value and its tolerance, including colour coding for resistors.

It provides coding for parameters specific either to capacitors, like e.g. the dielectric material, or to resistors, like e.g. the temperature coefficient of resistance (TCR).

It also provides date code systems suitable for the marking of small components.

## 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60063, *Preferred number series of resistors and capacitors*

IEC 60757, *Code for designation of colours*

ISO 8601, *Data elements and interchange formats – Information interchange – Representation of dates and times*

## 3 Colour code for fixed resistors

### 3.1 General rules

Colour code is applied in a sequence of individual solid colour bands.

Wherever possible, the first band shall be the one nearest to the end of the resistor and the bands shall be so placed and spaced that there can be no confusion in reading the coding.

The design width of the band used for marking the tolerance shall be at least 1,5 times the width of the other bands in order to avoid any confusion.

NOTE The design width is not intended to be measured.

Any additional coding shall be so applied as not to confuse the coding for value and tolerance.

Although colour bands are expected to be complete rings around the perimeter of a cylindrical resistor body, incidental interruption of a band shall be permissible if at least two thirds of the band is visible from any radial angle of view.

### 3.2 Prescription of code colours

The colours black, brown, red, orange, yellow, green, blue, violet, grey and white are used for the coding of the figures 0 through 9 for each significant numeral. Complemented with the