

JIS

JAPANESE
INDUSTRIAL
STANDARD

Translated and Published by
Japanese Standards Association

JIS B 8842 : 2020

(JCA/JSA)

**Cranes — Principles for seismically
resistant design**

ICS 53.020.20

Reference number : JIS B 8842 : 2020 (E)

PROTECTED BY COPYRIGHT

26 S

B 8842 : 2020

Date of Establishment: 2020-09-25

Date of Public Notice in Official Gazette: 2020-09-25

Investigated by: Japanese Industrial Standards Committee
Standards Board for ISO area

JIS B 8842 : 2020, First English edition published in 2021-11

Translated and published by: Japanese Standards Association
Mita MT Building, 3-13-12, Mita, Minato-ku, Tokyo, 108-0073 JAPAN

In the event of any doubts arising as to the contents,
the original JIS is to be the final authority.

© JSA 2021

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

HN

PROTECTED BY COPYRIGHT

Contents

	Page
Introduction	1
1 Scope	1
2 Normative references	2
3 Terms and definitions, and symbols	2
4 Concept of seismic design	5
4.1 General	5
4.2 Modified Seismic Coefficient Method	5
4.3 Maximum Response Spectrum Method	6
4.4 Time History Response Method	6
5 Calculation of seismic design loads by Modified Seismic Coefficient Method	7
5.1 General	7
5.2 Calculation of horizontal seismic design coefficient, K_H	7
5.3 Calculation of vertical seismic design coefficient, K_V	13
5.4 Calculation of seismic design loads	13
6 Calculation of seismic design loads based on Maximum Response Spectrum Method	14
6.1 General	14
6.2 Calculation procedure for total seismic response (<i>TSR</i>)	15
7 Combinations of seismic and non-seismic effects	17
7.1 General	17
7.2 Proof of static strength : load combinations in accordance with JIS B 8833-1	17
7.3 Proof of static strength : load combination according to SRSS Method	17
7.4 Proof of global stability	18
7.5 Proof of competence for crane structures	18
8 Calculation of seismic design loads by Time History Response Method	19
8.1 Calculation of seismic design loads using Level 1 earthquake ground motion	19
8.2 Calculation of seismic design loads using Level 2 earthquake ground motion	19
9 Base-isolated and vibration-controlled cranes	20
Annex A (informative) Seismic design by Modified Seismic Coefficient Method	21
Annex B (normative) Design accelerations	22

Annex C (informative)	Maximum Response Spectrum Method	24
Annex D (informative)	Time History Response Method and a comparison of Maximum Response Spectrum Method and Modified Seismic Coefficient Method	26
Annex E (informative)	Relation between basic acceleration, Mercalli and Richter scales	29
Annex F (informative)	Vertical influence factor	30
Annex JA (informative)	Calculation of subsoil amplification factor, β_2	31
Annex JB (informative)	Simple calculations of the natural period of a crane	33
Annex JC (informative)	Basic idea of risk factor, γ_n	36
Annex JD (informative)	Comparison table between JIS and corresponding In- ternational Standard	38

Foreword

This Japanese Industrial Standard has been established by the Minister of Health, Labour and Welfare and the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee according to the proposal for establishment of Japanese Industrial Standard submitted by Japan Crane Association (JCA)/Japanese Standards Association (JSA) with a draft being attached, based on the provision of Article 12, paragraph (1) of the Industrial Standardization Act.

This **JIS** document is protected by the Copyright Act.

Attention is drawn to the possibility that some parts of this Standard may conflict with patent rights, published patent application or utility model rights. The relevant Ministers and the Japanese Industrial Standards Committee are not responsible for identifying any of such patent rights, published patent application or utility model rights.

Cranes — Principles for seismically resistant design

Introduction

This Japanese Industrial Standard has been prepared based on ISO 11031 : 2016, Edition 1, with some modifications of the technical contents to take into account the specific seismic environment of Japan.

The vertical lines on both sides and dotted underlines indicate changes from the corresponding International Standard. A list of modifications with the explanations is given in Annex JD.

Because cranes are long and narrow structures, their capacity of absorbing earthquake energy via plastic deformation of their structural members at the time of an earthquake is considered to be generally less than that of building structures or the like, and this is an important point to be taken into consideration in designing seismically resistant cranes.

An economically acceptable protection against the effects of earthquake is usually based on two design limit states, serviceability limit state (SLS) and ultimate limit state (ULS), which specify the required crane response to a moderate earthquake that the crane may be exposed to during its service life and a severe earthquake that may occur at the installation site, and which are expressed in comparison to the ultimate limit states. Given the limited capacity of cranes to absorb seismic energy, this Standard treats the calculation of seismic design loads for the proof of competence in terms of SLS as mandatory, and that in terms of ULS as optional. The proof of competence in terms of SLS is based on the Modified Seismic Coefficient Method for a moderate earthquake.

1 Scope

This Standard provides requirements regarding the seismic loads and combination of seismic loads for crane structures of all the crane types (excluding mobile cranes) specified in **JIS B 0146** standard series or their structural members and machine elements (hereafter referred to as crane structural members).

This Standard evaluates dynamic response behaviour of a crane subjected to seismic excitation as a function of the dynamic characteristics of the crane and of its supporting structure. The evaluation takes into account dynamic effects both of regional seismic conditions and of the local conditions on the surface of the ground at the crane location.

The operational conditions of the crane and the risks resulting from seismic damage to the crane are also taken into account.

This Standard lays out the general concept of ULS, but does not extend to proofs of competence which include plastic deformations. When these are permitted by agreement between crane supplier and customer, other standards or relevant literature taking them into account can be used.