



**IEEE**

**IEC/IEEE 62704-1**

Edition 1.0 2017-10

# **INTERNATIONAL STANDARD**

**Determining the peak spatial-average specific absorption rate (SAR) in the human body from wireless communications devices, 30 MHz to 6 GHz –  
Part 1: General requirements for using the finite-difference time-domain (FDTD) method for SAR calculations**





## **THIS PUBLICATION IS COPYRIGHT PROTECTED**

**Copyright © 2017 IEC, Geneva, Switzerland**

**Copyright © 2017 IEEE**

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing being secured. Requests for permission to reproduce should be addressed to either IEC at the address below or IEC's member National Committee in the country of the requester or from IEEE.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland  
Tel.: +41 22 919 02 11  
Fax: +41 22 919 03 00  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

Institute of Electrical and Electronics Engineers, Inc.  
3 Park Avenue  
New York, NY 10016-5997  
United States of America  
[stds.ipr@ieee.org](mailto:stds.ipr@ieee.org)  
[www.ieee.org](http://www.ieee.org)

### **About the IEC**

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### **About the IEEE**

IEEE is the world's largest professional association dedicated to advancing technological innovation and excellence for the benefit of humanity. IEEE and its members inspire a global community through its highly cited publications, conferences, technology standards, and professional and educational activities.

### **About IEC/IEEE publications**

The technical content of IEC/IEEE publications is kept under constant review by the IEC and IEEE. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

#### **IEC Catalogue - [webstore.iec.ch/catalogue](http://webstore.iec.ch/catalogue)**

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

#### **IEC publications search - [www.iec.ch/searchpub](http://www.iec.ch/searchpub)**

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

#### **IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)**

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

#### **Electropedia - [www.electropedia.org](http://www.electropedia.org)**

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

#### **IEC Glossary - [std.iec.ch/glossary](http://std.iec.ch/glossary)**

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

#### **IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)**

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [csc@iec.ch](mailto:csc@iec.ch).



**IEEE**

**IEC/IEEE 62704-1**

Edition 1.0 2017-10

# **INTERNATIONAL STANDARD**

---

**Determining the peak spatial-average specific absorption rate (SAR) in the human body from wireless communications devices, 30 MHz to 6 GHz –  
Part 1: General requirements for using the finite-difference time-domain (FDTD) method for SAR calculations**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

---

ICS 17.220.20; 33.060.20

ISBN 978-2-8322-4769-3

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
2 Normative references .....	8
3 Terms and definitions .....	9
4 Abbreviated terms .....	15
5 Finite-difference time-domain method – basic definition.....	16
6 SAR calculation and averaging .....	17
6.1 Calculation of SAR in FDTD voxels .....	17
6.2 SAR averaging.....	18
6.2.1 General .....	18
6.2.2 Calculation of the peak spatial-average SAR .....	20
6.2.3 Calculation of the whole body average SAR.....	24
6.2.4 Reporting peak spatial-average SAR and whole body average SAR.....	24
6.2.5 Referencing peak spatial-average SAR and whole body average SAR.....	24
6.3 Power scaling .....	25
7 SAR simulation uncertainty.....	26
7.1 Considerations for the uncertainty evaluation.....	26
7.2 Uncertainty of the test setup with respect to simulation parameters .....	27
7.2.1 General .....	27
7.2.2 Positioning.....	27
7.2.3 Mesh resolution .....	28
7.2.4 Absorbing boundary conditions .....	29
7.2.5 Power budget .....	29
7.2.6 Convergence .....	29
7.2.7 Dielectrics of the phantom or body model .....	30
7.3 Uncertainty and validation of the developed numerical model of the DUT .....	31
7.3.1 General .....	31
7.3.2 Uncertainty of the DUT model ( $d \geq \lambda/2$ or $d \geq 200$ mm).....	31
7.3.3 Uncertainty of the DUT model ( $d < \lambda/2$ and $d < 200$ mm) .....	33
7.3.4 Model validation .....	34
7.4 Uncertainty budget.....	35
8 Code verification.....	36
8.1 General.....	36
8.2 Code accuracy.....	37
8.2.1 Free space characteristics .....	37
8.2.2 Planar dielectric boundaries .....	42
8.2.3 Absorbing boundary conditions.....	45
8.2.4 SAR averaging .....	48
8.3 Canonical benchmarks.....	50
8.3.1 Generic dipole .....	50
8.3.2 Microstrip terminated with ABC.....	51
8.3.3 SAR calculation SAM phantom / generic phone .....	52
8.3.4 Setup for system performance check .....	53
Annex A (normative) Fundamentals of the FDTD method .....	55
Annex B (normative) SAR Star.....	59

B.1	CAD files of the SAR Star .....	59
B.2	Mesh lines for the SAR Star .....	59
B.2.1	General .....	59
B.2.2	Mesh lines for the homogeneous SAR Star .....	59
B.2.3	Mesh lines for the inhomogeneous SAR Star .....	60
B.3	Evaluation of the SAR Star benchmark .....	60
B.3.1	General .....	60
B.3.2	File format of the benchmark output.....	60
B.3.3	Evaluation script.....	61
Annex C (informative)	Practical considerations for the application of FDTD .....	65
C.1	Overview.....	65
C.2	Practical considerations .....	66
C.2.1	Computational requirements .....	66
C.2.2	Voxel size .....	67
C.2.3	Stability .....	67
C.2.4	Absorbing boundaries .....	67
C.2.5	Far-zone transformation .....	68
C.3	Modelling requirements for sources and loads .....	68
C.4	Calculation of S-parameters.....	70
C.5	Calculation of power and efficiency.....	70
C.6	Non-uniform meshes .....	71
Annex D (informative)	Background information on tissue modelling and anatomical models.....	73
D.1	Dielectric tissue properties.....	73
D.2	Anatomical models of the human body.....	73
D.3	Recommended numerical models of experimental phantoms.....	73
D.3.1	Experimental head phantom .....	73
D.3.2	Experimental body phantom.....	74
Bibliography	.....	75
Figure 1	– Field components on voxel edges .....	17
Figure 2	– Flow chart of the SAR averaging algorithm.....	20
Figure 3	– Illustration of valid and used voxels in a valid averaging cube centred on the highlighted voxel and an invalid averaging volume for which a new cube has to be expanded about the surface voxel because it contains more than 10 % of background material .....	22
Figure 4	– Valid, used and partially used voxels .....	23
Figure 5	– “Unused” location.....	24
Figure 6	– Aligned parallel-plate waveguide and locations of the $E_y$ -field components to be recorded for TE-polarization.....	37
Figure 7	– Permissible power reflection coefficient (grey range) for the aligned absorbing boundary conditions .....	46
Figure 8	– Tilted parallel-plate waveguide terminated with absorbing boundary conditions and locations of the $E_y$ -field components to be recorded for TE-polarization .....	47
Figure 9	– Permissible power reflection coefficient (grey range) for the tilted absorbing boundary conditions.....	48
Figure 10	– Sketch of the testing geometry of the averaging algorithm.....	49
Figure 11	– 3D view of the SAR Star.....	50
Figure 12	– Geometry of the microstrip line.....	52

Figure 13 – Geometry of the setup for the system performance check according to [31]..... 53

Figure A.1 – Voxel showing the arrangement of the E- and H-field vector components on a staggered mesh ..... 57

Figure A.2 – Voxels with different dielectric properties surrounding a mesh edge with an  $E_y$ -component ..... 58

Figure C.1 – FDTD voltage source with source resistance ..... 69

Figure C.2 – Four magnetic field components surrounding the electric field component where the source is located ..... 69

  

Table 1 – Voxel states during SAR averaging ..... 22

Table 2 – Factors contributing to the uncertainty of experimental and numerical SAR evaluation ..... 27

Table 3 – Budget of the uncertainty contributions of the numerical algorithm and of the rendering of the test- or simulation-setup ..... 30

Table 4 – Budget of the uncertainty of the developed model of the DUT..... 34

Table 5 – Numerical uncertainty budget ..... 36

Table 6 – Results of the evaluation of the numerical dispersion characteristics ..... 42

Table 7 – Results of the evaluation of the numerical reflection coefficient ..... 44

Table 8 – Results of the dipole evaluation..... 51

Table 9 – Results of the microstrip evaluation..... 52

Table 10 – 1 g and 10 g psSAR for the SAM phantom exposed to the generic phone for 1 W accepted antenna power as specified in [22]..... 52

Table 11 – Dielectric parameters of the setup (Table 1 of [31]) ..... 54

Table 12 – Mechanical parameters of the setup (Tables 1 and 2 of [31])..... 54

Table 13 – psSAR normalized to 1 W forward power and feedpoint impedance (Tables 3 and 4 of [31]) ..... 54

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

---

### **DETERMINING THE PEAK SPATIAL-AVERAGE SPECIFIC ABSORPTION RATE (SAR) IN THE HUMAN BODY FROM WIRELESS COMMUNICATIONS DEVICES, 30 MHz TO 6 GHz –**

#### **Part 1: General requirements for using the finite-difference time-domain (FDTD) method for SAR calculations**

### FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation.

IEEE Standards documents are developed within IEEE Societies and Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of IEEE and serve without compensation. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information contained in its standards. Use of IEEE Standards documents is wholly voluntary. *IEEE documents are made available for use subject to important notices and legal disclaimers (see <http://standards.ieee.org/IPR/disclaimers.html> for more information).*

IEC collaborates closely with IEEE in accordance with conditions determined by agreement between the two organizations. This Dual Logo International Standard was jointly developed by the IEC and IEEE under the terms of that agreement.

- 2) The formal decisions of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees. The formal decisions of IEEE on technical matters, once consensus within IEEE Societies and Standards Coordinating Committees has been reached, is determined by a balanced ballot of materially interested parties who indicate interest in reviewing the proposed standard. Final approval of the IEEE standards document is given by the IEEE Standards Association (IEEE-SA) Standards Board.
- 3) IEC/IEEE Publications have the form of recommendations for international use and are accepted by IEC National Committees/IEEE Societies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC/IEEE Publications is accurate, IEC or IEEE cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications (including IEC/IEEE Publications) transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC/IEEE Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC and IEEE do not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC and IEEE are not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or IEEE or their directors, employees, servants or agents including individual experts and members of technical committees and IEC National Committees, or volunteers of IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board, for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC/IEEE Publication or any other IEC or IEEE Publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

9) Attention is drawn to the possibility that implementation of this IEC/IEEE Publication may require use of material covered by patent rights. By publication of this standard, no position is taken with respect to the existence or validity of any patent rights in connection therewith. IEC or IEEE shall not be held responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patent Claims or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

International Standard IEEE/IEC 62704-1 has been prepared by IEC technical committee 106: Methods for the assessment of electric, magnetic and electromagnetic fields associated with human exposure, in cooperation with the International Committee on Electromagnetic Safety of the IEEE Standards Association<sup>1</sup>, under the IEC/IEEE Dual Logo Agreement.

This publication is published as an IEC/IEEE Dual Logo standard.

This standard contains attached files in the form of CAD models and reference results described in Annexes B and D. These files are available at: [http://www.iec.ch/dyn/www/f?p=103:227:0:::FSP\\_ORG\\_ID,FSP\\_LANG\\_ID:1303,25](http://www.iec.ch/dyn/www/f?p=103:227:0:::FSP_ORG_ID,FSP_LANG_ID:1303,25).

The text of this standard is based on the following IEC documents:

FDIS	Report on voting
106/401A/FDIS	106/413/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

A list of all parts in the IEC/IEEE 62704 series, published under the general title *Determining the peak spatial-average specific absorption rate (SAR) in the human body from wireless communications devices, 30 MHz to 6 GHz*, can be found on the IEC website.

The IEC technical committee and IEEE technical committee have decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

---

<sup>1</sup> A list of IEEE participants can be found at the following URL:  
[http://standards.ieee.org/downloads/62704/62704-1-2017/62704-1-2017\\_wg-participants.pdf](http://standards.ieee.org/downloads/62704/62704-1-2017/62704-1-2017_wg-participants.pdf).

## INTRODUCTION

Computational techniques have reached a level of maturity which allows their use in specific absorption rate (SAR) assessment of wireless communication devices. Some wireless communication devices are used in situations where experimental SAR assessment is extremely complex or not possible at all. National regulatory bodies (e.g. US Federal Communications Commission) encourage the development of consensus standards and encouraged the establishment of the ICES Technical Committee 34 Subcommittee 2. The benefits to the users and the regulators include standardized and accepted protocols, anatomically correct body models, validation techniques, benchmark data, reporting format and means for estimating the computational uncertainty in order to produce valid, accurate, repeatable, and reproducible data.

# DETERMINING THE PEAK SPATIAL-AVERAGE SPECIFIC ABSORPTION RATE (SAR) IN THE HUMAN BODY FROM WIRELESS COMMUNICATIONS DEVICES, 30 MHz TO 6 GHz –

## Part 1: General requirements for using the finite-difference time-domain (FDTD) method for SAR calculations

### 1 Scope

This part of IEC/IEEE 62704 defines the methodology for the application of the finite-difference time domain (FDTD) technique when used for determining the peak spatial-average specific absorption rate (SAR) in the human body exposed to wireless communication devices with known uncertainty. It defines methods to validate the numerical model of the device under test (DUT) and to assess its uncertainty when used in SAR simulations. Moreover, it defines procedures to determine the peak spatial-average SAR in a cubical volume and to validate the correct implementation of the FDTD simulation software. The applicable frequency range is 30 MHz to 6 GHz.

NOTE Cubical averaging volumes are applied in all current experimental standards for the assessment of the peak spatial-average SAR (psSAR) and recommended by [1], [2] and [3]. Other averaging volumes have been proposed, for example, in [1], and may be included in future revisions of this document.

This document does not recommend specific SAR limits since these are found elsewhere, for example, in the guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP) [1] or in IEEE Std C95.1 [3].

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE The experimental standards that define the SAM phantom and the testing positions are IEEE Std 1528 and IEC 62209-1.

IEEE Std 1528, *IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques*

IEC 62209-1, *Human Exposure to Radio Frequency Fields from Hand Held and Body Mounted Wireless Communication Devices – Human Models, Instrumentation and Procedures – Part 1: Procedure to determine the specific absorption rate (SAR) for devices used next to the ear (frequency range of 300 MHz to 6 GHz)*

IEC 60050 (all parts), *International Electrotechnical Vocabulary (IEV)* (available at: <http://www.electropedia.org>)

IEEE Standards Dictionary Online (subscription available at: <http://dictionary.ieee.org>)